





|   |   |  |   |                                      |   |
|---|---|--|---|--------------------------------------|---|
| APPLICABLE STANDARD   |   | IEC 61076-3-124                                    |   |                                      |   |
| RATING  | Operating Temperature Range   | -40°C to +85°C(95%RH max)<br>(note1,2)             | Storage Temperature Range   | -30°C to +60°C(95%RH max)<br>(note1) |   |
|   | Voltage   | 50 V AC / 60 V DC                                  | Current   | 1.5 A/pin (all pin)                  |   |
|   |   |  |   | 3 A/pin (pin No.1,2,6,7)             |   |
| SPECIFICATIONS  |   |  |   |                                      |   |
| ITEM  |   | TEST METHOD  |   | REQUIREMENTS                         | QT AT   |
| CONSTRUCTION  |   |  |   |                                      |   |
| General Examination   |   | Examined visually and with a measuring instrument. |   | According to drawing.                | X X   |
| Marking   |   | Confirmed visually.                                |   | According to drawing.                | X X   |
| ELECTRIC CHARACTERISTICS  |   |  |   |                                      |   |
| Contact Resistance  | Measured at 100 mA max (DC or 1000 Hz).   |  | Contact : 30 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)  | X                                    | —   |
| Insulation Resistance   | Measured at 500 V DC.   |  |   | X                                    | —   |
| Voltage Proof   | 500 V DC applied for 1 min. Current leakage 2mA max.  |  | No flashover or breakdown.  | X                                    | —   |
| Insertion Loss  | Measured in the range of 1 to 500 MHz.  |  | 0.02 √(f) dB max.<br>(Whenever the formula results in a value less than 0.1 dB, the requirement shall revert to 0.1 dB.)  | X                                    | —   |
| Return Loss   | Measured in the range of 1 to 500 MHz.  |  | 68 – 20log(f) dB min.<br>(Whenever the formula results in a value greater than 30 dB, the requirement shall revert to 30 dB.)   | X                                    | —   |
| Near end Crosstalk  | Measured in the range of 1 to 500 MHz.  |  | 94 – 20log(f) dB min. (1MHz to 250MHz)<br>46.04 – 30log(f/250) dB min. (250MHz to 500MHz)<br>(Whenever the formula results in a value greater than 75 dB, the requirement shall revert to 75 dB.) | X                                    | —   |
| Far end crosstalk   | Measured in the range of 1 to 500 MHz.  |  | 83.1 – 20log(f) dB min.<br>(Whenever the formula results in a value greater than 75 dB, the requirement shall revert to 75 dB.)   | X                                    | —   |
| Transverse Conversion Loss  | Measured in the range of 1 to 500 MHz.  |  | 68 – 20log(f) dB min.<br>(Whenever the formula results in a value greater than 50 dB, the requirement shall revert to 50 dB.)   | X                                    | —   |
| Transverse Conversion Transfer Loss   | Measured in the range of 1 to 500 MHz.  |  | 68 – 20log(f) dB min.<br>(Whenever the formula results in a value greater than 50 dB, the requirement shall revert to 50 dB.)   | X                                    | —   |
| MECHANICAL CHARACTERISTICS  |   |  |   |                                      |   |
| Insertion and Withdrawal Forces   | A maximum rate of 50 mm/min.<br>Measured by applicable connector.                                     |  | Insertion force 25 N max.<br>Withdrawal force 25 N max.   | X                                    | —   |
| Mechanical Operation  | 5000 times insertions and extractions.<br><br>Mating speed : 10 mm/s max.<br>Rest : 5s, min.(unmated) |  | 1) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>2) No damage, cracks or looseness of parts.   | X                                    | —   |
| <div> <div>  </div> <div> <p>Note</p> <p>1. Non-condensing. 2. The operation temperature includes the temperature rise by current carrying</p> <p>3. The cable conductor resistance is not considered.</p> <p>4. Electrical characteristics are applicable to the contacts and shield except for contacts No. 3 and 6.</p> </div> </div> |   |  |   |                                      |   |
|   | COUNT   | DESCRIPTION OF REVISIONS                           | DESIGNED  | CHECKED                              | DATE  |
|    | 18  | DIS-E-00003730                                     | MT.YASUDA   | KI.KAGOTANI                          | 20210317  |
| REMARK  |   |  | APPROVED  | MN.KENJO                             | 20191209  |
|   |   |  | CHECKED   | KI.NAGANUMA                          | 20191209  |
|   |   |  | DESIGNED  | MT.YASUDA                            | 20191209  |
|   |   |  | DRAWN   | YK.MITSUISHI                         | 20191209  |
| Unless otherwise specified, refer to IEC 60512.   |   |  |   |                                      |   |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test  |   |  | DRAWING NO.   |                                      | ELC-129980-01-00  |
|    | SPECIFICATION SHEET   |  | PART NO.  | IX31G-B-10S-CVL1(7.0)(01)            |   |
|   | HIROSE ELECTRIC CO., LTD.   |  | CODE NO.  | CL0251-0068-0-01                     |  1/3 |

| SPECIFICATIONS   |  |  |                           |    |     |
|--|--|--|---------------------------|----|-----|
| ITEM   | TEST METHOD  | REQUIREMENTS   | QT                        | AT |     |
| ⚠<br>Vibration ,sinusoidal                                     | Frequency 10 to 500 Hz<br>0.35 mm, 50 m/s <sup>2</sup><br>2hrs in each of 3 mutually perpendicular axis. ⚠   | 1) No electrical discontinuity of 1μs. (note4)<br>2) No damage, cracks or looseness of parts.  | X                         | —  |     |
| Fretting Corrosion   | 490 m/s <sup>2</sup> , 30 times/min at 1000 times. ⚠   | 1) No electrical discontinuity of 1μs. (note4)<br>2) No damage, cracks or looseness of parts.  | X                         | —  |     |
| ⚠<br>Mechanical Shock  | Subject mated specimens to 300 m/s <sup>2</sup> half-sine shock pulses of 11 milliseconds duration, 3 shocks in both directions of 3 mutually perpendicular directions (totally 18 shocks) ⚠ | 1) No electrical discontinuity of 1μs. (note4)<br>2) Resistance:<br>Contact : 80 mΩ max. (note4)<br>Shield : 100 mΩ max. (note4)<br>3) No damage, cracks or looseness of parts.  | X                         | —  |     |
| ⚠<br>Effectiveness of the connector coupling device            | Applying 80 N force for the mating axis direction in state in fitted with applicable connector.  | No unlocking, damage, cracks or looseness of parts.  | X                         | —  |     |
| ⚠<br>Locking device mechanical operations                      | 10000 cycles<br>20 cycles/min max  | 1) Insertion and Withdrawal Forces<br>Insertion force 25 N max.<br>Withdrawal force 25 N max.<br>2) No damage, cracks or looseness of parts.   | X                         | —  |     |
| Wrenching Strength   | Applying 25times of 30 N 1s for 2 axis direction on tip of plug case in state in fitted with applicable connector.   | No damage, cracks or looseness of parts.   | X                         | —  |     |
| ENVIRONMENTAL CHARACTERISTICS                                  |  |  |                           |    |     |
| Rapid Change of Temperature<br>⚠                               | Subject mated specimens to 10 cycles between -55°C and 85°C with 30 minutes dwell at temp. extremes and 2 to 3 minutes transition between temperatures. ⚠                                    | 1) Voltage proof : 500 V DC applied for 1 min.<br>Current leakage 2mA max.<br>No flashover or breakdown.<br>2) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>3) Insulation resistance: 500 MΩ min. (at dry)<br>4) No damage, cracks or looseness of parts.  | X                         | —  |     |
| Humidity / Temperature Cycling                                 | Low temperature 25 °C;<br>High temperature 65 °C;<br>Cold sub-cycle - 10 °C;<br>Relative humidity 93 %<br>Duration 10 / each 24 h<br>(IEC 60068-2-38,test Z / AD) ⚠                          | 1) Voltage proof : 500 V DC applied for 1 min.<br>Current leakage 2mA max.<br>No flashover or breakdown.<br>2) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>3) Insulation resistance: 500 MΩ min. (at dry)<br>4) Insertion and Withdrawal Forces<br>Insertion force 25 N max.<br>Withdrawal force 25 N max.<br>5) No damage, cracks or looseness of parts. | X                         | —  |     |
| Damp Heat, Steady State  | Subject mated specimens to a relative humidity of 93 % at a temperature of 40°C during 21 days. ⚠  | 1) Voltage proof : 500 V DC applied for 1 min.<br>Current leakage 2mA max.<br>No flashover or breakdown.<br>2) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>3) Insulation resistance: 500 MΩ min. (at dry)<br>4) Insertion and Withdrawal Forces<br>Insertion force 25 N max.<br>Withdrawal force 25 N max.<br>5) No damage, cracks or looseness of parts. | X                         | —  |     |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test |  | DRAWING NO.  | ELC-129980-01-00          |    |     |
| <b>HRS</b>   | SPECIFICATION SHEET  | PART NO.   | IX31G-B-10S-CVL1(7.0)(01) |    |     |
|  | HIROSE ELECTRIC CO., LTD.  | CODE NO  | CL0251-0068-0-01          | ⚠  | 2/3 |

| SPECIFICATIONS   |  |  |  |              |  |  |    |   |     |
|--|--|--|--|--------------|--|--|----|---|-----|
| ITEM   |  | TEST METHOD  |  | REQUIREMENTS |  | QT   | AT |   |     |
| ENVIRONMENTAL CHARACTERISTICS                                  |  |  |  |              |  |  |    |   |     |
| Dry Heat   |  | Subject to +85 ± 2 °C, 21 days.<br>(mating applicable connector)   |  | ⚠            |  | 1) Voltage proof : 500 V DC applied for 1 min.<br>Current leakage 2mA max.<br>No flashover or breakdown.<br>2) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>3) Insulation resistance: 500 MΩ min. (at dry)<br>4) Insertion and Withdrawal Forces<br>Insertion force 25 N max.<br>Withdrawal force 25 N max.<br>5) No damage, cracks or looseness of parts. |    | X | —   |
| Cold   |  | Subject to -55 ± 3 °C, 10 days.<br>(mating applicable connector)   |  | ⚠            |  | 1) Voltage proof : 500 V DC applied for 1 min.<br>Current leakage 2mA max.<br>No flashover or breakdown.<br>2) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>3) Insulation resistance: 500 MΩ min. (at dry)<br>4) Insertion and Withdrawal Forces<br>Insertion force 25 N max.<br>Withdrawal force 25 N max.<br>5) No damage, cracks or looseness of parts. |    | X | —   |
| Corrosion Salt Mist  |  | Subject to 5 % salt water, 35 ± 2 °C, 48h.<br>(leave under unmated condition.)   |  |              |  | No heavy corrosion of contacts.  |    | X | —   |
| Mixed Flowing Gas Corrosion                                    |  | Test temperature : +25±1 °C, Relative humidity : 75±3 %<br>H <sub>2</sub> S : 10±5 ppb, NO <sub>2</sub> : 200±50 ppb<br>Cl <sub>2</sub> : 10±5 ppb, SO <sub>2</sub> : 200±20 ppb<br>Leave the samples for 4 days with mated.<br>The same is performed with unmated samples.<br>(IEC 60512, method 4) |  | ⚠            |  | 1) Resistance:<br>Contact : 80 mΩ max. (note3)<br>Shield : 100 mΩ max. (note3)<br>2) No damage, cracks or looseness of parts.  |    | X | —   |
|  |  |  |  |              |  |  |    |   |     |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test |  |  |  | DRAWING NO.  |  | ELC-129980-01-00   |    |   |     |
| HRS  |  | SPECIFICATION SHEET  |  | PART NO.     |  | IX31G-B-10S-CVL1(7.0)(01)  |    |   |     |
|  |  | HIROSE ELECTRIC CO., LTD.  |  | CODE NO      |  | CL0251-0068-0-01   |    | ⚠ | 3/3 |