





Sep.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window



POLARIZATION MARK



NOTE 1. 1PACK CONTAINS 270PCS.



2. ( )DIMENSIONS ARE ONLY REFERENCE.

△ 3. UL(File No. E132750) AUTHORIZATION ARTICLE.  
C-UL(File No. E132750) AUTHORIZATION ARTICLE.





	△數 COUNT	訂正事項 DESCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE		△數 COUNT	訂正事項 DESCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE
⚠	1	RE-6-1150	K.I.Y	L.S.M	18. 07. 04	⚠					. .
⚠	1	RE-6-1579	K.I.Y	L.S.M	20. 01. 23	⚠					. .
⚠					. .	⚠					. .

RECOMMENDED LAND PATTERN (FREE)  
(PCB THICKNESS t=1.6mm)



ENGAGEMENT FIGURE (2:1)



1	PBT	UL94V-0, BLACK	2	BRASS	TIN PLATING 1μm MIN, OVER NICKEL 0.5μm MIN
NO.	MATERIAL	FINISH,REMARKS	NO.	MATERIAL	FINISH,REMARKS
CODE NO. (OLD)			DRAWN	DESIGNED	CHECKED
			CHOI 18.03.02 J.S	CHOI 18.03.02 J.S	LIM 18.03.02 S.M
					KANG 18.03.02 T.S
					ENG 20.02.12 DEPT
DRAWING NO. EDC3-632473			PART NO. DF51K-4P-2DS (800)		
SCALE 4:1			CODE NO CL 6652-0061-3-800		
UNITS mm					