





- Notes
- ① The recommended tightening torque of ref.No. ① shall be 2 to 3N · m.  
LOCTITE 263, HENKEL JAPAN or equevalent is recommended to prevent  
ref. No. ① from loosening.
  - ② Across flats of hexagon hole of ref. No. ⑤ to be 1.27.  
The recommended tightening torque of ref.No. ⑤ shall be 0.3 to 0.4N · m.
  - ③ The cable pull and twisting strength(, waterproof tightness) and  
other characteristics may differ, depending on the cable structure,  
please confirm before the use.

3	Chloroprene rubber	(Black)						
2	Brass	Nickel plating	5	Stainless steel	JIS B 1177 Hexagon socket set screw M2.6×0.45×2			
1	Brass	Nickel plating	4	Brass	Nickel plating JIS B 1111 Pan head machine screw M3×0.5×8			
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	 COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00007459		DESIGNED TY. SUZUKI	CHECKED HY. KOBAYASHI	DATE 20211208
 HIROSE ELECTRIC CO., LTD.			APPROVED	HY. KOBAYASHI	20180222	DRAWING NO. EDC-112372-31-00		
			CHECKED	HY. KOBAYASHI	20180222	PART NO. RM24WTP-CP14(31)		
			DESIGNED	HY. KISHI	20180222	CODE NO. CL0109-1851-9-31		
			DRAWN	MK. INOUE	20180208	 1		