




- NOTE 1 COMPONENTS OF REF. NO. ①, ②, ⑧, ⑨ AND ⑩ ARE ASSEMBLED PARTS.  
2 COMPONENTS OF REF. NO. ⑤, ⑥ AND ⑦ ARE ASSEMBLED PARTS.  
3 COMPONENTS OF REF. NO. ③ AND ④ ARE ATTACHED PARTS.  
4 MECHANICAL OPERATION IS 100 TIMES EXCEPT GASKET AND CLAMP (COMPONENTS REF. NO. ③ AND ④).  
REPLACE REF. NO. ③ AND ④ WITH EACH TIME.  
5 Fig. 1 SHOWS THE APPEARANCE AFTER ASSEMBLY.  
6 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ① AND ⑤ TO BE 5 TO 5.5 N · m  
7 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,  
DEPENDING ON THE CABLE STRUCTURE, CONFIRM BEFORE USE.  
8 REFER TO ASSEMBLY PROCEDURE MANUAL ETAD-E3069.  
9 DO NOT INTEND TO PULL A COMPONENT OF REF. NO. ⑤, ⑥, ⑦ APART BY EXCESSIVE POWER.  
IT MAY CAUSE DISASSEMBLY.

5	POLYAMIDE	BLACK, UL94V-0	10	STAINLESS STEEL	
4	POLYAMIDE	NC, WHITE, UL94V-0	9	STAINLESS STEEL	
3	SILICONE RUBBER	BLACK	8	SILICONE RUBBER	RED
2	POLYAMIDE	BLACK, UL94V-0	7	STAINLESS STEEL	
1	POLYAMIDE	BLACK, UL94V-0	6	POLYAMIDE	BLACK, UL94V-0
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 1 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
			6	DIS-E-004629	SG. CHAMURA	EJ. WAKATSUKI	13. 04. 15

 HIROSE ELECTRIC CO., LTD.	APPROVED : RI. TAKAYASU	13. 01. 18	DRAWING NO.	EDC3-128149-00	
	CHECKED : EJ. WAKATSUKI	13. 01. 18	PART NO.	TM41W-P	
	DESIGNED : SG. CHAMURA	13. 01. 17	CODE NO.	CL222-2979-6-00	
	DRAWN : SG. CHAMURA	13. 01. 17			

