


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
APPLICABLE STANDARD												
RATING	OPERATING TEMPERATURE RANGE		-55℃ TO +85℃(note1)			STORAGE TEMPERATURE RANGE		-10℃ TO +60℃				
	VOLTAGE		30 V AC/DC			APPLICABLE CONNECTOR		BM23PF0.8-42DS-0.35V(**)				
	CURRENT		SIGNAL CONTACT 0.3A(note2) POWER CONTACT 5.0A									
SPECIFICATIONS												
ITEM		TEST METHOD				REQUIREMENTS				QT	AT	
CONSTRUCTION												
GENERAL EXAMINATION		CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				X	X	
MARKING		CONFIRMED VISUALLY.								X	X	
ELECTRICAL CHARACTERISTICS												
CONTACT RESISTANCE		20mV AC OR LESS 1kHz, 1mA				SIGNAL CONTACT : 90mΩ MAX POWER CONTACT : 30mΩ MAX				X	-	
INSULATION RESISTANCE		100V DC				50MΩ MIN				X	-	
VOLTAGE PROOF		100V AC FOR 1min.				NO FLASHOVER OR BREAKDOWN				X	-	
MECHANICAL CHARACTERISTICS												
MECHANICAL OPERATION		10 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: SIGNAL CONTACT : 90mΩ MAX POWER CONTACT : 30mΩ MAX ② NO DAMAGE, CRACK OR LOOSENESS OF PATRS.				X	-	
VIBRATION		FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min SINGLE AMPLITUDE 0.75mm, 10CYCLES, FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	-	
SHOCK		490 m/s² DURATION OF PULSE 11ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	-	
ENVIRONMENTAL CHARACTERISTICS												
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → +85℃ TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN2~3 MIN)				① CONTACT RESISTANCE: SIGNAL CONTACT : 90mΩ MAX POWER CONTACT : 30mΩ MAX ② INSULATION RESISTANCE: 50MΩ MIN ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	-	
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2℃, 90 TO 95%, 96h.				① CONTACT RESISTANCE: SIGNAL CONTACT : 90mΩ MAX POWER CONTACT : 30mΩ MAX ② INSULATION RESISTANCE: 25MΩ MIN ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	-	
SULPHUR DIOXIDE		EXPOSED IN 25 PPM FOR 96h, 25℃, 75±5%RH. (Test standard : JIS C 60068)				① CONTACT RESISTANCE: SIGNAL CONTACT : 90mΩ MAX POWER CONTACT : 30mΩ MAX ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	-	
REMARKS												
Note 1 : INCLUDE THE TEMPERATURE RISING BY CURRENT. Note 2 : MAX 12A AT TOTAL PIN CONTACTS.						DRAWN S.H.JUNG 17.05.10		DESIGNED S.H.JUNG 17.05.10		CHECKED H.W.JO 17.05.10		
Unless otherwise specified, refer to JIS C 5402 and IEC 60512						APPROVED T.S.KANG 17.05.10		RELEASED 17.05.10				
Note QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST												
HIROSE KOREA CO.,LTD.				SPECIFICATION SHEET				PART NO. BM23PF0.8-42DP-0.35V(895)				
CODE NO.(OLD) CL				DRAWING NO. SLC4-632162				CODE NO. CL 6644-0080-3-895				1/1