

APPLICABLE STANDARD																
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTE 1)		STORAGE TEMPERATURE RANGE	-10°C TO + 60°C											
	VOLTAGE	50V AC		APPLICABLE CONNECTOR	DF17# (**)-*DS-0.5V (**)											
	CURRENT	0.3A														
SPECIFICATIONS																
ITEM		TEST METHOD		REQUIREMENTS	QT AT											
CONSTRUCTION																
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X											
MARKING		CONFIRMED VISUALLY.			X X											
ELECTRIC CHARACTERISTICS																
CONTACT RESISTANCE		100m A (DC OR 1000 Hz).		60mΩ MAX.	X —											
INSULATION RESISTANCE		100V DC.		500MΩ MIN.	X —											
VOLTAGE PROOF		150V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	X —											
MECHANICAL CHARACTERISTICS																
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.		<table border="1"> <thead> <tr> <th rowspan="2">SIGNAL</th> <th>INSERTION FORCE</th> <th>WITHDRAWAL FORCE</th> </tr> <tr> <th>(N)MAX</th> <th>(N)MIN</th> </tr> </thead> <tbody> <tr> <td>26</td> <td>26.0</td> <td>2.6</td> </tr> <tr> <td>80</td> <td>80.0</td> <td>8.0</td> </tr> </tbody> </table>	SIGNAL	INSERTION FORCE	WITHDRAWAL FORCE	(N)MAX	(N)MIN	26	26.0	2.6	80	80.0	8.0	X —
SIGNAL	INSERTION FORCE	WITHDRAWAL FORCE														
	(N)MAX	(N)MIN														
26	26.0	2.6														
80	80.0	8.0														
MECHANICAL OPERATION		50TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 60mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —											
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —											
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —											
ENVIRONMENTAL CHARACTERISTICS																
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→ 5 TO 35→ 85→ 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —											
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —											
CORROSION SALT MIST		EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X —											
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JEIDA-39)		① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X —											
HEAT RESISTANCE OF SOLDERING		[RECOMMENDED TEMPERATURE PROFILE] 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 90 ~ 120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDELING CONDITION] SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X —											
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE											
△																
REMARKS			APPROVED	MO. NAKAMURA	05.12.17											
NOTE1: INCLUDING THE TEMPERATURE RISE BY CURRENT.			CHECKED	TS. MIYAZAKI	05.12.17											
			DESIGNED	YH. MICHIDA	05.12.16											
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.			DRAWN	HK. MURAKAMI	05.12.16											
Note QT: Qualification Test AT: Assurance Test X: Applicable Test			DRAWING NO.		ELC4-163276-07											
SPECIFICATION SHEET			PART NO.	DF17B (2. 5) -*DP-0. 5V (57)												
HIROSE ELECTRIC CO., LTD.			CODE NO.	CL683	△ 1/1											