Sep.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	VOLTAGE		APPLICABLE CABLE	1 CABLE DIAMETER : φ6.9±0.5
	CURRENT			

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	1	DIS-E-00011415	KIM JAEHYEON	KG.OKITA	20221013

REMARK

Unless otherwise specified, refer to JIS C 5402.

APPROVED	AO.SUZUKI	20090507
CHECKED	KN.ICHIKAWA	20090507
DESIGNED	MO.SHIMOYAMA	20090507
DRAWN	MO.SHIMOYAMA	20090507

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-126674-00

HRS	SPECIFICATION SHEET	PART NO.	DH-27-CMB(6.9)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL0244-0036-9-00	1 1/1

FORM HD0011-2-1