






APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE	-55°C TO +85°C	STORAGE TEMPERATURE RANGE	-10°C TO +50°C(PACKED CONDITION)			
	VOLTAGE	30V AC/DC	OPERATING OR STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 90%MAX(NOT DEWED)			
	CURRENT	0.2 A	APPLICABLE CABLE	t=0.2±0.02mm, GOLD PLATING			
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS	QT AT		
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	×	×	
MARKING		CONFIRMED VISUALLY.			×	×	
ELECTRICAL CHARACTERISTICS							
VOLTAGE PROOF		90V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	×	×	
INSULATION RESISTANCE		100V DC.		50MΩ MIN.	×	×	
CONTACT RESISTANCE		AC 20mV MAX (1KHz), 1mA.		200mΩ MAX. INCLUDING FPC BULK RESISTANCE (L=8mm)	×	×	
MECHANICAL CHARACTERISTICS							
VIBRATION		FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75 mm FOR 10 CYCLES IN 3 AXIAL DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μ s. ② CONTACT RESISTANCE: 200mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—	
SHOCK		981 m/s ² , DURATION OF PULSE 6ms AT 3 TIMES IN 3 BOTH AXIAL DIRECTIONS.			×	—	
MECHANICAL OPERATION		10 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 200mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—	
FPC RETENTION FORCE		MEASURED BY APPLICABLE FPC. (THICKNESS OF FPC SHALL BE t=0.20mm AT INITIAL CONDITION.)		DIRECTION OF INSERTION: 4 + 0.1 × n N MIN. (note 1)	×	—	
ENVIRONMENTAL CHARACTERISTICS							
CORROSION SALT MIST		EXPOSED AT 35±2°C, 5% SALT WATER SPRAY FOR 96h.		① CONTACT RESISTANCE: 200mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. ③ NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.	×	—	
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→+15 TO +35→+85→+15 TO +35 °C TIME 30 → 2 TO 3 → 30 → 2 TO 3 min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 200mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2°C, RELATIVE HUMIDITY 90 TO 95%, 96h.				×	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
							
REMARK				APPROVED	NF.MIYAZAKI	15.07.30	
				CHECKED	YN.TAKASHITA	15.07.30	
				DESIGNED	YH.MICHIDA	15.07.29	
				DRAWN	NM.SANPEI	15.07.29	
Unless otherwise specified, refer to IEC 60512.							
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-365495-00-00		
	SPECIFICATION SHEET		PART NO.	FH43MW-**S-0.25SHW(10)			
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL580		1/2	

SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
DAMP HEAT, CYCLIC	EXPOSED AT -10 TO +65 °C RELATIVE HUMIDITY 90 TO 96 % 10 CYCLES, TOTAL 240h.	① CONTACT RESISTANCE: 200mΩ MAX. ② INSULATION RESISTANCE: 1MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 50MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—	
DRY HEAT	EXPOSED AT 85±2°C, 96h.	① CONTACT RESISTANCE: 200mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—	
COLD	EXPOSED AT -55±3°C, 96h.		×	—	
SULPHUR DIOXIDE [JIS C 60068-2-42]	EXPOSED AT 40±2°C, RELATIVE HUMIDITY 80±5 %, 25±5 ppm FOR 96h.	① CONTACT RESISTANCE: 200mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—	
HYDROGEN SULPHIDE [JIS C 60068-2-43]	EXPOSED AT 40±2°C, RELATIVE HUMIDITY 80±5 %, 10 TO 15 ppm FOR 96h.	③ NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.	×	—	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 245±3°C FOR IMMERSION DURATION, 3±0.3 sec.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.	×	—	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING: PEAK TMP. 250°C MAX. REFLOW TMP. OVER 230°C WITHIN 60 sec. 2) SOLDERING IRONS: TMP. 350±10°C FOR 5±1 sec.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. (note 2)	×	—	
<div>(note 1)</div> <div>THIS PRODUCT HAS FLIP-LOCK CONSTRUCTION. FASTEN FPC ON PCB OR SOMETHING FIXED IF FORCE IN VERTICAL DIRECTION SHALL BE PREDICTED.</div> <div>(note 2)</div> <div>BLISTERS WHICH MAY OCCUR IN HOUSING DO NOT AFFECT PRODUCT PERFORMANCE.</div>					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-365495-00-00		
	SPECIFICATION SHEET	PART NO.	FH43MW-**S-0.25SHW(10)		
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL580		2/2