



| | | | | | |
|--|-----------------------------|---|-------------------------------------|---|------------------|
| APPLICABLE STANDARD | | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -40 °C TO 105 °C | STORAGE TEMPERATURE RANGE | -40 °C TO 105 °C (MOUNTED ON PCB) | |
| | VOLTAGE | 50 V AC / DC | OPERATING OR STORAGE HUMIDITY RANGE | RELATIVE HUMIDITY 90 % MAX (NOT DEWED) | |
| | CURRENT | 0.5 A (note 1) | APPLICABLE CABLE | t=0.3±0.05mm, GOLD PLATING | |
| SPECIFICATIONS | | | | | |
| ITEM | | TEST METHOD | | REQUIREMENTS | QT AT |
| CONSTRUCTION | | | | | |
| GENERAL EXAMINATION | | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | × |
| MARKING | | CONFIRMED VISUALLY. | | | × |
| ELECTRICAL CHARACTERISTICS | | | | | |
| CONTACT RESISTANCE | | 1mA(DC OR 1000Hz). | | 50 mΩ MAX. INCLUDING FPC,FFC BULK RESISTANCE (L=8mm) | × |
| INSULATION RESISTANCE | | 100 V DC. | | 500 MΩ MIN. | × |
| VOLTAGE PROOF | | 150 V AC FOR 1 min. | | NO FLASHOVER OR BREAKDOWN. | × |
| MECHANICAL CHARACTERISTICS | | | | | |
| MECHANICAL OPERATION | | 20 TIMES INSERTIONS AND EXTRACTIONS. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × |
| VIBRATION | | FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75 mm, FOR 10 CYCLES IN 3 AXIAL DIRECTIONS. | | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② CONTACT RESISTANCE: 50 mΩ MAX. | × |
| SHOCK | | 981 m/s ² , DURATION OF PULSE 6 ms AT 3 TIMES IN 3 BOTH AXIAL DIRECTIONS. | | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × |
| FPC RETENTION FORCE | | MEASURED BY APPLICABLE FPC. (CONNECTOR,FPC AT INITIAL CONDITION. THICKNESS OF FPC SHALL BE t=0.30mm) | | DIRECTION OF INSERTION: 0.4×n N MIN (n : NUMBER OF CONTACTS). | × |
| ENVIRONMENTAL CHARACTERISTICS | | | | | |
| RAPID CHANGE OF TEMPERATURE | | TEMPERATURE -40→+15T ₀ +35→+105→+15T ₀ +35°C TIME 30→ 2 T ₀ 3 → 30 → 2 T ₀ 3 min. UNDER 5 CYCLES. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 50 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × |
| DAMP HEAT (STEADY STATE) | | EXPOSED AT 40±2 °C, RELATIVE HUMIDITY 90 TO 95 %, 96 h. | | | × |
| DAMP HEAT,CYCLIC | | EXPOSED AT -10 TO +65 °C, RELATIVE HUMIDITY 90 TO 96 %, 10 CYCLES,TOTAL 240 h. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 50 MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × |
| DRY HEAT | | EXPOSED AT 105±2 °C, 96 h. | | ① CONTACT RESISTANCE: 50 mΩ MAX. | × |
| COLD | | EXPOSED AT -40±3°C, 96 h. | | ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × |
| CORROSION SALT MIST | | EXPOSED AT 35±2 °C 5% SALT WATER SPRAY FOR 96 h. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. | × |
| SULPHUR DIOXIDE [JIS C 60068-2-42] | | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% , 25±5 ppm FOR 96 h. | | | × |
| HYDROGEN SULPHIDE [JIS C 60068-2-43] | | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% , 10 TO 15 ppm FOR 96 h. | | | × |
| COUNT | DESCRIPTION OF REVISIONS | | DESIGNED | CHECKED | DATE |
| 0 | | | | | |
| REMARK | | | APPROVED | NF. MIYAZAKI | 15. 03. 24 |
| STORAGE TEMPERATURE RANGE IN THE EMBOSSED CARRIER TAPE : -10 TO +50 °C | | | CHECKED | HS. SAKAMOTO | 15. 03. 24 |
| Unless otherwise specified, refer to JIS C 5402. | | | DESIGNED | HK. KINOUCHI | 15. 03. 24 |
| | | | DRAWN | HK. KINOUCHI | 15. 03. 24 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC-363488-00-00 |
| HRS | SPECIFICATION SHEET | | PART NO. | FH52E-*(*) SA-1SH | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL580 | △ 1/2 |

| SPECIFICATIONS | | | | | |
|--|---|--|-------------|--------------------|---|
| ITEM | TEST METHOD | REQUIREMENTS | QT | AT | |
| RESISTANCE TO SOLDERING HEAT | 1) REFLOW SOLDERING (TO BE 2 TIMES MAX.) PEAK TMP. 250 °C MAX REFLOW TMP. OVER 230 °C WITHIN 60 sec. PRE-HEATING. 150 TO 200°C 90 TO 120 sec. 2)SOLDERING IRONS : 350 ± 10 °C, FOR 5± 1 sec . | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | X | — | |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE, 245±3 °C FOR IMMERSION DURATION, 3±0.3 sec. | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | X | — | |
| <p>(note 1)</p> <p>WHEN THE SAME VALUE OF CURRENT ARE APPLIED TO ALL CONTACTS AT THE SAME TIME IN ONCE, SET THE CURRENT TO THE 70 % OF THE RATED CURRENT VALUE.</p> | | | | | |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC-363488-00-00 |
|  | SPECIFICATION SHEET | | PART NO. | FH52E-* (*) SA-1SH | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO | CL580 |  2/2 |