





APPLICABLE STANDARD													
 RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C <sup>(1) (2)</sup>	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C <sup>(3)</sup>									
	VOLTAGE	60 V AC <sup>(5)</sup>	OPERATING HUMIDITY RANGE	RH 85 % MAX <sup>(2) (4)</sup>									
	CURRENT	0.5 A <sup>(5)</sup>	STORAGE HUMIDITY RANGE	RH 70 % MAX <sup>(3) (4)</sup>									
	APPLICABLE CABLE	AWG 36, 40 THIN COAXIAL CABLE											
SPECIFICATIONS													
ITEM		TEST METHOD		REQUIREMENTS		QT	AT						
CONSTRUCTION													
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		x	x						
MARKING		CONFIRMED VISUALLY.				x	x						
<div>REMARKS</div> <div>(1) INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING. (2) OPERATING TEMPERATURE SHOULD BE -55 TO 40°C WHEN HUMIDITY EXCEEDS 80% RH. (3) THE SPECIFICATION IS APPLIED TO THE PRE-ASSEMBLED COMPONENT AND THE CABLE ASSEMBLED PRODUCT BOTH IN DELIVERY AND STORAGE, BEFORE ASSEMBLED TO PCB. (4) THERE MUST NOT BE DEWFALL. (5) IT IS THE MAXIMUM VALUE OF CONNECTOR. CONFIRM THE SPECIFICATION OF THE CABLE.</div> <div>Unless otherwise specified, refer to JIS-C-5402.</div>													
								APPROVED		HS. OKAWA		08. 05. 24	
								CHECKED		HT. YAMAGUCHI		08. 05. 24	
								DESIGNED		TS. SHIBUYA		08. 05. 24	
								DRAWN		TS. SHIBUYA		08. 05. 24	
Note		QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-158279-00							
		SPECIFICATION SHEET		PART NO.		FX16-21P-GNDL							
		HIROSE ELECTRIC CO., LTD.		CODE NO.		CL575-3331-8-00							
							1/1						