

| COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|-------|--------------------------|----|------|------|-------|--------------------------|----|------|------|
| △ | | | | | △ | | | | |
| △ | | | | | △ | | | | |

| | | | | |
|---------------------|-----------------------------|--------------------------------|---------------------------|--------------------------------|
| APPLICABLE STANDARD | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C ⁽¹⁾ | STORAGE TEMPERATURE RANGE | -10 °C TO 60 °C ⁽²⁾ |
| | VOLTAGE | 125 V AC | OPERATING HUMIDITY RANGE | 40 % TO 80 % |
| | CURRENT | 0.5 A | STORAGE HUMIDITY RANGE | 40 % TO 70 % ⁽²⁾ |

| SPECIFICATIONS | | | | |
|----------------|-------------|--------------|----|----|
| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |

| | | | | |
|---------------------|---------------------------------------|--|-----------------------|---|
| CONSTRUCTION | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | |
| MARKING | CONFIRMED VISUALLY. | | × | × |

| | | | | |
|---|-------------------------------|----------------------------|---|--|
| ELECTRICAL CHARACTERISTICS | | | | |
| CONTACT RESISTANCE | 100 mA (DC OR 1000 Hz). | 45 mΩ MAX. | × | |
| CONTACT RESISTANCE MILLIVOLT LEVEL METHOD | 20 mV MAX, 1 mA(DC OR 1000Hz) | 55 mΩ MAX. | × | |
| INSULATION RESISTANCE | 250 V DC. | 100 MΩ MIN. | × | |
| VOLTAGE PROOF | 300 V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | × | |


| | | | | |
|----------------------------|--|--|---|--|
| MECHANICAL CHARACTERISTICS | | | | |
| MECHANICAL OPERATION | 500 TIMES INSERTIONS AND EXTRACTATIONS. | ① CONTACT RESISTANCE: 55 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × | |
| VIBRATION | FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.52 mm, AT 2 h FOR 3 DIRECTION. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × | |
| SHOCK | 490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | | × | |

| | | | | |
|-------------------------------|---|---|---|--|
| ENVIRONMENTAL CHARACTERISTICS | | | | |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h. | ① CONTACT RESISTANCE: 55 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN. | × | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE-55→+15~+35→+85→+15~+35°C TIME 30 → 10~15 → 30 → 10~15 min UNDER 5 CYCLES. | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × | |
| CORROSION SALT MIST | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h. | ① CONTACT RESISTANCE: 55 mΩ MAX. ② NO HEAVY CORROSION. | × | |
| HYDROGEN SULPHIDE | EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38) | | × | |
| RESISTANCE TO SOLDERING HEAT | 1) SOLDER BATH:SOLDER TEMPERATURE, 260±5°C FOR IMMERSION,DURATION,10±1s. 2) SOLDERING IRONS : 360°C FOR 5 s. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL. | × | |
| SOLDRABILITY | SOLDERED AT SOLDER TEMPERATURE 240±3°C FOR IMMERSION DURATION, 2s. | A NEW UNIFORM COATING OF SOLDER SHALL OVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | × | |

| | | | | | |
|--|-----------|------------|----------|----------|----------|
| REMARKS | DRAWN | DESIGNED | CHECKED | APPROVED | RELEASED |
| 1)TEMPERATURE RISE INCLUDED WHEN ENERGIZED. 2)THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. | I.OKAYAMA | K.NAKAMURA | H.Okawa | H.Okawa | |
| | 04.06.09 | 04.06.09 | 04.06.09 | 04.06.09 | |

Unless otherwise specified, refer to MIL-STD-1344.

Note QT:Qualification Test AT:Assurance Test ×:Applicable Test

| | | | |
|--|----------------------------|-------------------------|-----|
|  HIROSE ELECTRIC CO., LTD. | SPECIFICATION SHEET | PART NO. | |
| | | FX2C2-**P-1. 27DSA (71) | |
| CODE NO.(OLD) | DRAWING NO. | CODE NO. | |
| CL | ELC4 - 083049-21 | CL 572 | 1/1 |