

| COUNT | DESCRIPTION OF REVISIONS | BY  | CHKD | DATE     | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|-------|--------------------------|-----|------|----------|-------|--------------------------|----|------|------|
| △ 2   | RE-F-09653               | K.N | H.Y  | 04.04.06 | △     |                          |    |      |      |
| △ 1   | RE-F-10251               | K.D | H.O  | 05.02.02 | △     |                          |    |      |      |

|                     |                             |                 |                           |                 |
|---------------------|-----------------------------|-----------------|---------------------------|-----------------|
| APPLICABLE STANDARD |                             |                 |                           |                 |
| RATING              | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C | STORAGE TEMPERATURE RANGE | -10 °C TO 60 °C |
|                     | VOLTAGE                     | 100 V AC        | OPERATING HUMIDITY RANGE  | 40 % TO 80 %    |
|                     | CURRENT                     | 0.4 A           | STORAGE HUMIDITY RANGE    | 40 % TO 70 %    |

| SPECIFICATIONS  |   |  |                                |  |
|---|---|--|--------------------------------|--|
| ITEM  | TEST METHOD   | REQUIREMENTS   | QT                             | AT   |
| CONSTRUCTION  |   |  |                                |  |
| GENERAL EXAMINATION   | VISUALLY AND BY MEASURING INSTRUMENT.   | ACCORDING TO DRAWING.  | ×                              | ×  |
| MARKING   | CONFIRMED VISUALLY.   |  | ×                              | ×  |
| ELECTRIC CHARACTERISTICS  |   |  |                                |  |
| CONTACT RESISTANCE  | 100 mA (DC OR 1000 Hz).   | 80 mΩ MAX. <sup>(1)</sup>  | ×                              |  |
| CONTACT RESISTANCE MILLIVOLT LEVEL METHOD   | 20 mV MAX, 1 mA(DC OR 1000Hz)   | 100 mΩ MAX. <sup>(2)</sup>   | ×                              |  |
| INSULATION RESISTANCE   | 250 V DC.   | 100 MΩ MIN.  | ×                              |  |
| VOLTAGE PROOF   | 300 V AC FOR 1 min.   | NO FLASHOVER OR BREAKDOWN.   | ×                              |  |
| MECHANICAL CHARACTERISTICS  |   |  |                                |  |
| MECHANICAL OPERATION  | 50 TIMES INSERTIONS AND EXTRACTIONS.  | ① CONTACT RESISTANCE: 100 mΩ MAX. <sup>(2)</sup><br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | ×                              |  |
| VIBRATION   | FREQUENCY 10 TO 55 Hz,<br>AMPLITUDE : 1.5 mm,<br>AT 2 h FOR 3 DIRECTION.                                    | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② CONTACT RESISTANCE: 100 mΩ MAX. <sup>(2)</sup>     | ×                              |  |
| SHOCK   | 490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms<br>AT 3 TIMES FOR 3 DIRECTIONS.                              | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.   | ×                              |  |
| ENVIRONMENTAL CHARACTERISTICS   |   |  |                                |  |
| DAMP HEAT (STEADY STATE)  | EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.  | ① CONTACT RESISTANCE: 100 mΩ MAX. <sup>(2)</sup><br>② INSULATION RESISTANCE: 100 MΩ MIN.       | ×                              |  |
| RAPID CHANGE OF TEMPERATURE   | TEMPERATURE-55→+15~+35→+85→+15~+35°C<br>TIME 30 → 2~3 → 30 → 2~3 min<br>UNDER 5 CYCLES.                     | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.   | ×                              |  |
| CORROSION SALT MIST   | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.   | ① CONTACT RESISTANCE: 100 mΩ MAX. <sup>(2)</sup><br>② NO HEAVY CORROSION.                      | ×                              |  |
| HYDROGEN SULPHIDE   | EXPOSED IN 3 PPM FOR 96 h.<br>(TEST STANDARD: JEIDA-38)   |  | ×                              |  |
| RESISTANCE TO SOLDERING HEAT  | 1) REFLOW SOLDERING : 250 °C MAX,<br>: 220 °C MIN,<br>FOR 60 s<br>2) SOLDERING IRONS : 360 °C, △<br>FOR 5 s | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.                                | ×                              |  |
| SOLDERABILITY △<br>△  | SOLDERED AT SOLDER TEMPERATURE, 240 ± 3°C,<br>FOR IMMERSION DURATION, 3 s.                                  | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.   | ×                              |  |
| REMARKS <sup>(1)</sup> THIS CONNECTOR'S INITIAL CONTACT RESISTANCE SHALL BE 80 mΩ, BECAUSE OF THE BULK RESISTANCE OF STACKING HEIGHT 16 mm TYPE.<br><sup>(2)</sup> AFTER TEST, THE CHANGE OF THE CONTACT RESISTANCE SHALL BE 20 mΩ MAX. |   |  |                                |  |
| DRAWN<br>S.SUZUKI<br>03.02.13   |   | DESIGNED<br>K.NAKAMURA<br>03.02.13   | CHECKED<br>H.OKAWA<br>03.02.14 | APPROVED<br>Y.YOSHIMURA<br>03.02.15                |
| Released  |   |  |                                |  |
| Note QT:Qualification Test AT:Assurance Test ×:Applicable Test  |   |  |                                |  |
| HS HIROSE ELECTRIC CO., LTD.  |   | SPECIFICATION SHEET  |                                |  |
| CODE NO.(OLD)<br>CL   |   | DRAWING NO.<br>ELC4 - 151089- 23   |                                | PART NO.<br>FX8C-※※P-SV4(93)<br>CODE NO.<br>CL 578 |
|   |   |  |                                | 1<br>1   |