

<b>APPLICABLE STANDARD</b>					
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-40 °C TO +120 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C <sup>(1)</sup>	
	CURRENT	30 A	STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 85% MAX (NOT DEWED)	
	VOLTAGE	600 V AC/DC			
<b>SPECIFICATIONS</b>					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	x	x
MARKING		CONFIRMED VISUALLY.		x	x
<b>ELECTRIC CHARACTERISTICS</b>					
CONTACT RESISTANCE		10A DC.	POWER:3mΩ/SIGNAL:10mΩ /SHIELD:50mΩ MAX.	x	—
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV AC MAX, 10mA(DC OR 1000Hz)	POWER:3mΩ/SIGNAL:10mΩ /SHIELD:50mΩ MAX.	x	—
INSULATION RESISTANCE		1000 V DC.	100 MΩ MIN.	x	—
VOLTAGE PROOF		2500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	x	—
<b>MECHANICAL CHARACTERISTICS</b>					
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: POWER:5mΩMAX/SIGNAL:20mΩMAX ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x	—
VIBRATION		FREQUENCY 20 TO 200Hz (88m/s <sup>2</sup> ) SWEEP TIME 3min.(ROUND TRIP) AT 3h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 7ΩMIN , 1μs MIN. ② CONTACT RESISTANCE: POWER:5mΩMAX/SIGNAL:20mΩMAX ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x	—
LOCK STRENGTH		MEASURE BREAK STRENGTH OF THE LOCK BY PULLING THE CONNECTOR IN THE MATING DIRECTION.	98N MIN.	x	—
DESTRUCTION TORQUE		WHEN ACTUAL MEASURED PANEL, PLEASE TIGHTEN A SCREW. M4 SCREW BE USED, 2.88N · m(MAX)	WITHOUT DESTRUCTION	x	—
<b>ENVIRONMENTAL CHARACTERISTICS</b>					
DAMP HEAT (STEADY STATE)		EXPOSED AT 85 °C, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: POWER:5mΩMAX/SIGNAL:20mΩmax ② INSULATION RESISTANCE:100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE- 40 →ROOM TEMP →120°C→ ROOM TEMP TIME 30 → 5 → 30 → 5 min UNDER 1000 CYCLES.	① CONTACT RESISTANCE: POWER:5 mΩ MAX. ② INSULATION RESISTANCE:100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x	—
DRY HEAT		EXPOSED AT 125°C, 300 h.	① CONTACT RESISTANCE: POWER:5mΩMAX/SIGNAL:20mΩMAX ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x	—
COLD		EXPOSED AT -40°C , 120 h.	① CONTACT RESISTANCE: POWER:5mΩMAX/SIGNAL:20mΩMAX ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x	—
RESISTANCE TO SO <sub>2</sub> GAS		EXPOSED IN 25 PPM AT 75% MIN FOR 96h.	CONTACT RESISTANCE: POWER:5mΩMAX/SIGNAL:20mΩMAX	x	—
WATERPROOFNESS		SINKING TO WATER AFTER EXPOSED AT 125°C WITH CONNECTORS MATED AND ATTACHED TO RECOMMENDED PANEL.	NO WATER IS INSIDE THE CONNECTOR.	x	—
①	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK (NOTE1) "STORAGE" means a long-term storage state for the unused product.			APPROVED	HK. UMEHARA	20180928
			CHECKED	AH. EDASHIGE	20180928
			DESIGNED	TS. SHIMIZU	20180928
			DRAWN	DS. HIROWATARI	20180926
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-377226-00-00
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	HVH-280-2/2P-HU (A)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL778-0510-0-00	① 1/1