

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-40 °C TO +120 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C ⁽¹⁾	
	CURRENT	30 A	STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 85% MAX	
	VOLTAGE	600 V AC/DC		(NOT DEWED)	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	x x
MARKING		CONFIRMED VISUALLY.			x x
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE		10 A DC.	3 mΩ MAX.		x -
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV AC MAX, 10 mA(DC OR 1000Hz)	3 mΩ MAX.		x -
INSULATION RESISTANCE		1000 V DC.	100 MΩ MIN.		x -
VOLTAGE PROOF		2500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN		x -
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 5 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x - x -
VIBRATION		FREQUENCY 20 TO 400Hz (43.1m/s ²) SWEEP TIME 3min.(ROUND TRIP) AT 3h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 7ΩMIN , 1μs MIN. ② CONTACT RESISTANCE: 5 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x - x - x -
LOCK STRENGTH		MEASURE BREAK STRENGTH OF THE LOCK BY PULLING THE CONNECTOR IN THE MATING DIRECTION.	98N MIN.		x -
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)		EXPOSED AT 60 °C, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: 5 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x - x - x -
RAPID CHANGE OF TEMPERATURE		TEMPERATURE- 40 → ROOM TEMP → 120°C → ROOM TEMP TIME 30 → 5 → 30 → 5 min UNDER 100 CYCLES.	① CONTACT RESISTANCE: 5 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x - x - x -
DRY HEAT		EXPOSED AT 125°C, 300 h.	① CONTACT RESISTANCE: 5 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x - x -
COLD		EXPOSED AT -40°C , 120 h.	① CONTACT RESISTANCE: 5 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x - x -
RESISTANCE TO SO ₂ GAS		EXPOSED IN 25 PPM AT 75% MIN FOR 96h.	CONTACT RESISTANCE: 5 mΩ MAX.		x -
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
△					
REMARK			APPROVED	HK. UMEHARA	20180928
NOTE1) "STORAGE" means a long-term storage state for the unused product.			CHECKED	AH. EDASHIGE	20180928
			DESIGNED	TS. SHIMIZU	20180928
			DRAWN	DS. HIROWATARI	20180926
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-382042-00-00
HRS	SPECIFICATION SHEET		PART NO.	HVH-280-2P/S-R	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL778-0705-0-00	△ 1/1