

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-55°C TO +125°C(95%RH MAX)		STORAGE TEMPERATURE RANGE	-55°C TO +125°C(95%RH MAX)
	POWER	_____ W		CHARACTERISTIC IMPEDANCE	50 Ω (0.045 TO 65 GHz)
	PECULIARITY	_____		APPLICABLE CABLE	_____
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MARKING		CONFIRMED VISUALLY.			- -
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100 mA MAX (DC OR 1000 Hz).	CENTER CONTACT	16 mΩ MAX.	X	X
		OUTER CONTACT	16 mΩ MAX.	X	X
INSULATION RESISTANCE	250 V DC.	500 MΩ MIN.		X	X
VOLTAGE PROOF	250 V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.		NO FLASHOVER OR BREAKDOWN.	X	X
RETURN LOSS	FREQUENCY 0.045 TO 65 GHz.	RETURN LOSS	15dB MIN : 0.045 TO 40 GHz 10dB MIN : 40 TO 65 GHz	X	X
INSERTION LOSS	FREQUENCY TO GHz	dB MAX.		-	-
MECHANICAL CHARACTERISTICS					
CONTACT INSERTION AND EXTRACTION FORCES	[SMPM SIDE] φ0.32 +0.0025 0 BY STEEL GAUGE.	INSERTION FORCE	6.7 N MAX.	X	-
		EXTRACTION FORCE	N MIN	-	-
	[SMPM SIDE] φ0.2896 +0.0025 0 BY STEEL GAUGE.	INSERTION FORCE	N MAX.	-	-
		EXTRACTION FORCE	0.1 N MIN	X	X
	[HV SIDE] φ0.495 0 -0.005 BY STEEL GAUGE.	INSERTION FORCE	N MAX.	-	-
		EXTRACTION FORCE	0.2 N MIN	X	X
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR. [APPLICABLE CONNECTOR : SMPMP(FD)-HVP]		INSERTION FORCE	26.7 N MAX.	X -
			EXTRACTION FORCE	13.4 N MIN	X -
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.		1) CONTACT RESISTANCE: CENTER CONTACT 28 mΩMAX.CHANGE OUTER CONTACT 28 mΩMAX.CHANGE 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
VIBRATION	FREQUENCY 10 TO 500 Hz SINGLE AMPLITUDE 0.75 mm, 98 m/s <sup>2</sup> AT 10 CYCLES FOR 3 DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 1μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			X	-
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)	APPLYING A PULL FORCE THE CABLE AXIALLY AT N MAX.		1) NO WITHDRAWAL AND BREAKAGE OF CABLE. 2) NO BREAKAGE OF CLAMP.	-	-
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT,CYCLIC	EXPOSED AT -10 TO +65 °C, 90~98% TOTAL 10 CYCLES ( 240 h )		1) INSULATION RESISTANCE: 100 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 500 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -65 → --- → +125 → --- °C TIME 30 → 3 → 30 → 3 min. UNDER 5 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h		NO HEAVY CORROSION	X	-
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
0					
REMARK			APPROVED	MH. YAMANE	08.07.19
RoHS COMPLIANT			CHECKED	TS. NOBE	08.07.18
			DESIGNED	RO. YOKOYAMA	08.07.18
Unless otherwise specified, refer to JIS C 5402.			DRAWN	RO. YOKOYAMA	08.07.18
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-313093-00
HRS	SPECIFICATION SHEET		PART NO.	SMPMJ-HVJ	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL311-0421-7-00	△ 1/1