

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△	5	RE-5-1833	OCU	CDH	17. 11. 30	△					
△	1	RE-5-2459	OCU	CDH	20. 07. 15	△					
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE		-55℃ ~ +85℃			STORAGE TEMPERATURE RANGE		-10℃ ~ +50℃(Packed Condition)			
	VOLTAGE		50V [AC(rms) / DC]			OPERATING OR STORAGE HUMIDITY RANGE		Relative Humidity 90% MAX(NOT DEWED)			
	CURRENT		0.5A [AC(rms) / DC] (note1)			APPLICABLE CABLE		△ FFC/FPC (t=0.2±0.03mm)			
SPECIFICATIONS											
ITEM		TEST METHOD				REQUIREMENTS			QT	AT	
CONSTRUCTION											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT				ACCORDING TO DRAWING			O	O	
MARKING		CONFIRMED VISUALLY							O	O	
ELECTRICAL CHARACTERISTICS											
CONTACT RESISTANCE		MATE APPLICABLE FPC/FFC AND APPLY A CURRENT OF 1mA DC(OR 1,000Hz)				100 mΩ MAX. INCLUDING FPC/FFC BULK RESISTANCE(L=8mm)			O	O	
INSULATION RESISTANCE		MATE APPLICABLE FPC/FFC AND APPLY A VOLTAGE OF DC 100V				500 MΩ MIN.			O	O	
VOLTAGE PROOF		MATE APPLICABLE FPC/FFC AND APPLY A VOLTAGE OF AC 150V FOR 1 min.				NO FLASHOVER OR BREAKDOWN.			O	O	
MECHANICAL CHARACTERISTICS											
FPC RETENSION FORCE		MEASURE BY APPLICABLE FPC/FFC(t=0.2) AT INITIAL CONDITION				①VERTICAL DIRECTION : 0.25N X n MIN. △ ②HORIZONTAL DIRECTION : 0.25N X n MIN.			O	-	
MECHANICAL OPERATION		20 TIMES INSERTIONS AND EXTRACTIONS				①CONTACT RESISTANCE: 100mΩ MAX ②NO DAMAGE,CRACK AND LOOSENESS OF PARTS			O	-	
VIBRATION		FREQUENCY 10 ~ 55 Hz, HALF AMPLITUDE 0.75 mm AT 2h, IN 3 DIRECTIONS				①NO ELECTRICAL DISCONTINUITY OF 1μs. ②CONTACT RESISTANCE : 100mΩ MAX			O	-	
SHOCK		981m/s ² DIRECTION OF PULSE 6ms AT 3 TIMES IN 3 DIRECTIONS.				③NO DAMAGE,CRACK AND LOOSENESS OF PARTS			O	-	
ENVIRONMENTAL CHARACTERISTICS											
DAMP HEAT(STEADY STATE)		EXPOSED AT 40℃, 90~95 %, 96Hr.				①CONTACT RESISTANCE: 100 mΩ MAX.			O	-	
RAPID CHAGE OF TEMPERATURE		TEMPERATURE : -55 → 15~35 → +85 → 15~35 ℃ TIME : 30 → 2~3 → 30 → 2~3 min. 5 CYCLES WITH ABOVE CONDITIONS. △				②INSULATION RESISTANCE: 100 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			O	-	
DAMP HEAT, CYCLE		TEMPERATURE -10→+65 HUMIDITY : 90~95% 10 CYCLE(240Hr)				①CONTACT RESISTANCE: 100mΩ MAX. ②INSULATION RESISTANCE: 100 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			O	-	
DRY HEAT		EXPOSED AT 85℃, 96Hr				①CONTACT RESISTANCE : 100mΩ MAX			O	-	
COLD		EXPOSED AT -55℃, 96Hr				②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			O	-	
CORROSION SALT SPRAY		EXPOSED AT 35℃, 5 % SALT WATER SPRAY FOR 96Hr				①CONTACT RESISTANCE 100mΩ MAX ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			O	-	
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96Hr. (TEST STANDARD : JEIDA-38)				③NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.			O	-	
RESISTANCE TO SOLDERING HEAT		PROFILE : 250℃ MAX. △ 230℃ WITHIN 60 sec				①NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. ②NO DAMAGE OF ELECTRICAL PERFORMANCE			O	-	
SOLDER ABILITY △		SOLDER DIPPING TEMPERATURE 245±5℃ (TEST STANDARD : MIL-STD-202) 3±0.3 SEC				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMERSSED.			O	-	
(note 1) △ WHEN THE SAME VALUE OF CURRENT ARE APPLIED TO ALL CONTACTS AT THE SAME TIME IN ONCE, SET THE CURRENT TO THE 70% OF THE RATED CURRENT VALUE.											
REMARKS		CONDITIONS FOR TESTING			DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
					OH.C.U 17. 03. 06	OH.C.U 17. 03. 06	CHO.D.H 17. 03. 06	SONG.H.C 17. 03. 06	<div style="border: 2px solid red; border-radius: 50%; padding: 10px; text-align: center; color: red;"> ENG 2020.07.15 DEPT </div>		
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.											
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST O: APPLICABLE TEST											
HIROSE KOREA CO.,LTD.			REFERENCE SPECIFICATION SHEET				PART NO. TF13BSA-SERIES (800)				
CODE NO.(OLD)		DRAWING NO. ELC4-632309-80			CODE NO. CL 6508-0037-2-800			1/1			