

APPLICABLE STANDARD		ANSI/TIA/EIA-568-B.2.10 CAT6a			
RATING	OPERATING TEMPERATURE RANGE	① -25 °C TO 60 °C	STORAGE TEMPERATURE RANGE	-25 °C TO 60 °C	
	VOLTAGE	125 V AC	OPERATING HUMIDITY RANGE	95 % MAX	
	CURRENT	1 A	APPLICABLE CABLE	—	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MARKING		CONFIRMED VISUALLY.			X X
<div>① THE OPERATION TEMPERATURE INCLUDES THE TEMPERATURE RISE BY CURRENT CARRYING.</div> <div>② TEMPERATURE RANGE FOR A CONNECTOR UNMATED.</div> <div>③ USE UNDER THE CONDITION RECOMMENDED BY A CABLE MANUFACTURE.</div>					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
REMARK			APPROVED	YH. ENAMI	09.06.02
			CHECKED	YH. ENAMI	09.06.02
			DESIGNED	MT. ITANO	09.06.02
			DRAWN	MT. ITANO	09.06.02
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126868-02
HRS	SPECIFICATION SHEET		PART NO.	TM31P-TM-88P (02)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-4626-7-02	△ 1/1