



NOTE 1. COPLANARITY OF SMT TERMINAL SHALL BE 0.1 MAXIMUM.
NOTE 2. PRODUCTION LOT NUMBER IS MARKED AS SHOWN.
(LOT No. Ex.)

9 0 2 8
| 生産日 DAY (01~31)
| 生産月 MONTH (1~9, Oct:0, Nov:X, Dec:Y)
| 生産年 (西暦下1桁) YEAR (LAST DIGIT ONLY)

4	SHELL	1	STEEL ALLOY	TIN PLATING	—
3	CONTACT B	9	COPPER ALLOY	CONTACT AREA: GOLD OVER NICKEL SOLDER TAILS: GOLD FLASH OVER NICKEL	CONTACT AREA: 0.1 μm Min. SOLDER TAILS: 0.03 μm Min.
2	CONTACT A	10	COPPER ALLOY	—	COLOR: BLACK
1	INSULATOR	1	HEAT RESISTING PLASTICS	—	—

仕様書 (SPECIFICATION) JACS-30402 JABL-30402	第1版 (ORIGINAL DATE) 28/OCT/2019	尺度 (SCALE) 5:1	シリーズ (SERIES) DC04	日本航空電子工業株式会社
一般公差 (GENERAL TOLERANCE)	製図 DR.	名称 (TITLE) DC04S019JAA	質量 (MASS)	JAE JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.
寸法 (DIMENSION)	担当 CHK.	承認 APPD.	図面番号 (DRAWING NO.) SJ121498	版数 (VER.) 1
角度 (ANGLES)	承認 APPD.	承認 APPD.		
単位 (UNIT): mm				