XGST2020

Portable diagnostic terminal, Radio frequency identification XG, RFID diagnostics 13.56 MHz

Main

Range of Product	Telemecanique Radio frequency identification XG
Product or Component Type	Portable diagnostic terminal
RFID diagnostic terminal name	XGST
Processor name	CPU ARM7

Complementary

RFID Frequency	13.56 MHz
Terminal use	Diagnostics on compact stations Read / write operations on tags
[Us] rated supply voltage	5 V DC AC external adaptor 3.7 V DC internal battery
Autonomy	8 h
Memory description	Expandable USB memory stick, up to 2 GB Internal data storage Compact Flash, 2 GB Internal RAM RAM/SDRAM, 256 kB
Display Type	OLED colour touchscreen
Display size	54 x 95 mm
Pixel resolution	480 x 272 pixels
Status LED	1 LED charging
Communication port support	USB RS485 non isolated
Marking	CE
Net Weight	0.65 lb(US) (0.295 kg)

Environment

Product Certifications	CE
Ambient air temperature for operation	32…113 °F (0…45 °C)
Ambient Air Temperature for Storage	-4…113 °F (-20…45 °C)
Relative humidity	5…95 %
IP Degree of Protection	IP40

Ordering and shipping details

Category	22491 - SENS,IDENTIFICATION DEVICE (XGK)
Discount Schedule	DS2
GTIN	3389119081436
Nbr. of units in pkg.	1
Package weight(Lbs)	13.58 oz (385 g)
Returnability	No
Country of origin	FR

Life Is On | Schneider Electric

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.09 in (5.3 cm)
Package 1 width	3.50 in (8.9 cm)
Package 1 Length	6.46 in (16.4 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	6
Package 2 Weight	5.59 lb(US) (2.535 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months

Dimensions

RFID Handheld Terminal