Data sheet

SIEMENS

3SU1001-0AB50-0AA0-Z Y13



Illuminated pushbutton, 22 mm, round, plastic, blue, pushbutton, flat momentary contact type, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

product brand name	SIRIUS ACT	
product designation	Illuminated pushbuttons	
design of the product	Actuating/signaling element	
product type designation	3SU1	
product line	Plastic, black, 22 mm	
Enclosure		
number of command points	1	
Actuator		
design of the actuating element	Flat button	
principle of operation of the actuating element	momentary contact type	
product extension optional		
light source	Yes	
contact module	Yes	
color of the actuating element	blue	
material of the actuating element	plastic	
shape of the actuating element	round	
outer diameter of the actuating element	29.5 mm	
marking of the actuating element	Customized labeling, graphical symbols acc. to ISO7000 and IEC60417	
Front ring		
product component front ring	Yes	
design of the front ring	Standard	
material of the front ring	plastic	
color of the front ring	black	
General technical data		
protection class IP	IP66, IP67, IP69(IP69K)	
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance		
• acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms	
 for railway applications acc. to DIN EN 61373 	Category 1, Class B	
vibration resistance		
• acc. to IEC 60068-2-6	10 500 Hz: 5g	
● for railway applications acc. to DIN EN 61373	Category 1, Class B	
	3 600 1/h	
operating frequency maximum		
operating frequency maximum mechanical service life (switching cycles) typical	3 000 000	
	3 000 000 S	
mechanical service life (switching cycles) typical		

 ambient temperature during storage 	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	11 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AB50-0AA0-Z Y13

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-0AB50-0AA0-Z Y13

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AB50-0AA0-Z Y13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AB50-0AA0-Z Y13&lang=en

last modified: 12/21/2020 🖸