

Specification Sheet

Part Number: 102-69067



The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

Bundling Clip with Arrowhead, 1.5" Long, 0.03 - 0.05" Panel Thickness, PA66HIRHS, Black, 500/pkg

Article Number 102-69067

Type ATSBCKSFT6.5

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties.

Short Description Bundling Clip with Arrowhead, 1.5" Long, 0.03 - 0.05" Panel Thickness, PA66HIRHS, Black, 500/pkg

Global Part Name ATSBCKSFT6.5-PA66HIRHS-BK

Length L (Imperial)	1.5
Length L (Metric)	39.0
Fixation Method	Arrowhead (Small Mount)
Width W (Imperial)	0.354
Width W (Metric)	9.0
Bundle Diameter Max (Imperial)	0.75
Bundle Diameter Max (Metric)	20.0
Power supply unit	Electrical
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.05
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	1.3
Mounting Hole Diameter D (Imperial)	0.25 - 0.28
Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26

Mounting Hole Diameter D Max (Metric) 6.7

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

UV Resistant (Yes/No) No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

