

## Specification Sheet

Part Number: T18MR0C2



Screw mount style creates low insertion and high extraction force. Choose from several tensile strengths and lengths to accommodate a range of applications.

1-Piece Cable Tie/Screw Mount, 4.3" Long, #4 Screw, 0.79" Max Bundle Dia, 18lb, PA66HS, Black, 100/pkg

Article Number 113-00022

Type T18MR

Color Black (BK)

Quantity Per bag

Product Description 1-piece Screw Mount Cable Ties fasten with a screw or bolt to provide secure routing of cable bundles. Multiple configurations are available to cover a range of bundle sizes and tensile strengths.

Short Description 1-Piece Cable Tie/Screw Mount, 4.3" Long, #4 Screw, 0.79" Max Bundle Dia, 18lb, PA66HS, Black, 100/pkg

Global Part Name T18MR-PA66HS-BK

|                                     |                 |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 18.0            |
| Minimum Tensile Strength (Metric)   | 80              |
| Length L (Imperial)                 | 4.3             |
| Length L (Metric)                   | 110.0           |
| Fixation Method                     | Fixing hole     |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.1             |
| Width W (Metric)                    | 2.5             |
| Bundle Diameter Min (Imperial)      | 0.06            |
| Bundle Diameter Min (Metric)        | 1.5             |
| Bundle Diameter Max (Imperial)      | 0.8             |
| Bundle Diameter Max (Metric)        | 20.0            |
| Thickness T (Imperial)              | 0.039           |

|                                       |        |
|---------------------------------------|--------|
| Thickness T (Metric)                  | 1.0    |
| Height H (Imperial)                   | .17    |
| Height H (Metric)                     | 4.20   |
| Mounting Hole Diameter D (Imperial)   | 0.12   |
| Mounting Hole Diameter D (Metric)     | 3.1 mm |
| Mounting Hole Diameter D Max (Metric) | 3.1    |

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V-2

UV Resistant (Yes/No) No

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Certification/Specification UL 62275

UL Recognized (US) Yes

|                               |            |
|-------------------------------|------------|
| UL Listed (US and Canada)     | Yes        |
| UL Recognized (US and Canada) | Yes        |
| UL Listed (US)                | Yes        |
| Package Quantity (Imperial)   | 100        |
| Package Quantity (Metric)     | 100        |
| Customs Number                | 3926909988 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)