

#### **MIRELLA-50-W**

~40° wide beam

#### **SPECIFICATION:**

Dimensions Ø 49.9 mm
Height 23.9 mm
Fastening glue
ROHS compliant yes ①

#### **MATERIALS:**

ComponentTypeMaterialMIRELLA-50-WReflectorPC



ColourFinishCoatingmetallacquer

#### **ORDERING INFORMATION:**

Component


C12478\_MIRELLA-50-W

» Box size: 480 x 280 x 300 mm

**Qty in box MOQ MPQ Box weight (kg)** 336 112 28 3.0



# PRODUCT DATASHEET C12478\_MIRELLA-50-W



See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>






LED BXRA LS
FWHM / FWTM 42.0° / 78.0°
Efficiency 84 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C13333\_MIRELLA-CL



#### bridgelux.


LED BXRA LS
FWHM / FWTM 35.0° / 78.0°
Efficiency 88 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



#### bridgelux

LED BXRA LS
FWHM / FWTM 43.0° / 78.0°
Efficiency 82 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479\_MIRELLA-DL






## **CITIZEN**

LED CLL01x FWHM / FWTM 44.0° / 85.0°

Efficiency %
LEDs/each optic 1
Light colour White
Required components:







## **CITIZEN**

LED CLL01x FWHM / FWTM 50.0° / 86.0°

Efficiency %
LEDs/each optic 1
Light colour White
Required components:
C12479\_MIRELLA-DL



## **CITIZEN**

LED CLL01x
FWHM / FWTM 48.0° / 80.0°
Efficiency 84 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White


Light colour Whit Required components: C13333\_MIRELLA-CL



## **CITIZEN**

LED CLL02x/CLU02x (LES10)

FWHM / FWTM 50.0° / 84.0°
Efficiency 83 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479\_MIRELLA-DL



## **CITIZEN**

LED CLL02x/CLU02x (LES10)

FWHM / FWTM 42.0° / 82.0°
Efficiency 90 %
LEDs/each optic 1
Light colour White
Required components:







## **CITIZEN**

CLL02x/CLU02x (LES10)

FWHM / FWTM 50.0° / 87.0° Efficiency 82 % Peak intensity 1 cd/lm LEDs/each optic Light colour White Required components: C13723\_MIRELLA-RZL





## **CITIZEN**

CLL02x/CLU02x (LES10)

FWHM / FWTM 48.0° / 82.0° Efficiency 82 % LEDs/each optic 1 White Light colour Required components: C12479\_MIRELLA-DL



## **CITIZEN**

CLL02x/CLU02x (LES10)

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 46.0° / 78.0° Efficiency 84 % Peak intensity 1.2 cd/lm LEDs/each optic Light colour White Required components: C13333\_MIRELLA-CL




## **CITIZEN**


CLU700/701/702/703

FWHM / FWTM 46.0° / 83.0° Efficiency 80 % Peak intensity 1.1 cd/lm LEDs/each optic White Light colour Required components: C13723\_MIRELLA-RZL

















# **CITIZEN**


CLU720/721/723  $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 53.0° / 90.0° Efficiency 80 % Peak intensity 0.9 cd/lm LEDs/each optic

Light colour White Required components: C13723\_MIRELLA-RZL




## **CITIZEN**

LED CLU720/721/723 FWHM / FWTM 51.0° / 85.0° Efficiency 88 % Peak intensity 1.1 cd/lm LEDs/each optic 1 White Light colour Required components:



# **CITIZEN**

LED CLU720/721/723  $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 53.0° / 88.0° Efficiency 79 % Peak intensity 0.9 cd/lm LEDs/each optic Light colour White Required components: C12479\_MIRELLA-DL



## CREE 🕏

CXA/B 13xx FWHM / FWTM 43.0° / 76.0° Efficiency 81 % Peak intensity 1.4 cd/lm LEDs/each optic White Light colour Required components:

C12479\_MIRELLA-DL





# CREE &

LED CXA/B 13xx
FWHM / FWTM 37.0° / 80.0°
Efficiency 86 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



# CREE \$


LED CXA/B 13xx
FWHM / FWTM 42.0° / 76.0°
Efficiency 81 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333\_MIRELLA-CL



# CREE +


LED CXA/B 15xx
FWHM / FWTM 50.0° / 82.0°
Efficiency 87 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C12479\_MIRELLA-DL



## CREE \$

LED CXA/B 15xx
FWHM / FWTM 42.0° / 84.0°
Efficiency 91 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:





# CREE &

LED CXA/B 15xx
FWHM / FWTM 46.0° / 79.0°
Efficiency 85 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White

Required components: C13333\_MIRELLA-CL



# CREE -

LED CXA/B 1816 & CXA/B 1820 & CXA 1850

FWHM / FWTM 56.0° / 84.0°
Efficiency 82 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C13333\_MIRELLA-CL



# CREE +

LED CXA/B 1816 & CXA/B 1820 & CXA 1850

FWHM / FWTM 52.0° / 84.0°
Efficiency 82 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479\_MIRELLA-DL




## CREE \$

LED CXA/B 1816 & CXA/B 1820 & CXA 1850


FWHM / FWTM 52.0° / 88.0°
Efficiency 87 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:























#### **MUMILEDS**

LED LUXEON S1000
FWHM / FWTM 34.0° / 75.0°
Efficiency 84 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333\_MIRELLA-CL



#### LUMILEDS

LED LUXEON \$1000 FWHM / FWTM 34.0° / 79.0°

Efficiency %
LEDs/each optic 1
Light colour White
Required components:



## **MATERIAL PROPERTY OF THE PROP**

LED LUXEON S1000 FWHM / FWTM 41.0° / 79.0°


Efficiency %
LEDs/each optic 1
Light colour White
Required components:
C12479\_MIRELLA-DL




#### **ELUMINUS**

LED CxM-9 (13.5x13.5) FWHM / FWTM 49.0° / 81.0° Efficiency 83 %

Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479\_MIRELLA-DL








17/24










LED NSCxL036A FWHM / FWTM 46.0° / 80.0° Efficiency 83 % Peak intensity 1.3 cd/lm LEDs/each optic Light colour White Required components: C12479\_MIRELLA-DL





#### **OSRAM**

LED Duris S10 FWHM / FWTM 49.0° / 86.0° Efficiency 79 % Peak intensity 1.1 cd/lm LEDs/each optic 1 White Light colour Required components: C12479\_MIRELLA-DL



# OSRAM Opto Semiconductors

LED Duris S10  $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 40.0° / 84.0° Efficiency 87 % Peak intensity 1.5 cd/lm LEDs/each optic Light colour White Required components:




#### **OSRAM**


LED Duris S10 FWHM / FWTM 45.0° / 79.0° Efficiency 82 % Peak intensity 1.3 cd/lm LEDs/each optic White Light colour Required components: C13333\_MIRELLA-CL


















#### **OPTICAL RESULTS (SIMULATED):**




LED Vero SE 10 FWHM / FWTM 32.0° / 72.0°

Efficiency 91 % Peak intensity 2 cd/lm LEDs/each optic

Light colour White

Required components:




#### **MUMILEDS**

LED LUXEON 7070 FWHM / FWTM 46.0° / 83.0 + 82.0°

Efficiency 96 % Peak intensity 1.4 cd/lm LEDs/each optic 1 White Light colour


Required components:



# OSRAM Opto Semiconductors

LED OSCONIQ P 7070 FWHM / FWTM 45.0° / 84.0° Efficiency 91 % Peak intensity 1.4 cd/lm LEDs/each optic 1 Light colour White

Required components:




#### **OSRAM**

LED Soleriq S9

FWHM / FWTM 50.0° / 78.0° 87 % Efficiency Peak intensity 1.2 cd/lm LEDs/each optic White Light colour

Required components: C13333\_MIRELLA-CL





## **OPTICAL RESULTS (SIMULATED):**



LED

Soleriq S9

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 

51.0° / 81.0°

Efficiency

Peak intensity

1.1 cd/lm


LEDs/each optic

85 %

White

Light colour Required components:

C13723\_MIRELLA-RZL



#### **OSRAM**

LED

Soleriq S9

FWHM / FWTM

47.0° / 83.0°

Efficiency

91 %


Peak intensity

1.3 cd/lm

LEDs/each optic Light colour

1 White

Required components:



# OSRAM Opto Semiconductors

LED

Soleriq S9

FWHM / FWTM

51.0° / 80.0°

Efficiency

85 %


Peak intensity LEDs/each optic 1.1 cd/lm

Light colour

1 White

Required components:

C12479\_MIRELLA-DL





# PRODUCT DATASHEET C12478\_MIRELLA-50-W

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

24/24

www.ledil.com/ where\_to\_buy