

Specification Sheet

Part Number: 126-00426



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Cable tie is outside serrated to reduce bundle chafing.

1-Piece Cable Tie & Edge Clip, 8" Long, EC34, Panel Thickness .04"-.12", 50 lbs, PA66HS, Black, 500/bg

Article Number

126-00426

Type

T50SOSEC34E

Color

Black (BK)

Quantity Per

bag

Product Description

HellermannTyton's Cable Tie with Edge Clip is designed to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure, and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. This fastener is molded as a one-piece clip and tie combination.

Short Description

1-Piece Cable Tie & Edge Clip, 8" Long, EC34, Panel Thickness .04"-.12", 50 lbs, PA66HS, Black, 500/bg

Global Part Name T50SOSEC34E-PA66HS-BK

Minimum Tensile Strength (Imperial) 40.0

Minimum Tensile Strength (Metric) 180

Length L (Imperial) 6.0

Length L (Metric) 155.0

Fixation Method Edge Clips

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.4

Bundle Diameter Max (Metric) 35.0

Height H (Imperial)	0.06
Height H (Metric)	1.35
Panel Thickness Min (Imperial)	0.039
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	1.00
Panel Thickness Max (Metric)	3.00

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V-2

UV Resistant (Yes/No) No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number

3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)