

## Specification Sheet

Part Number: 133-02353



Bundling clip with gradual transition provides security to bundles around panel edges.

Flanged ends prevent slip in tape wrap.

4x oval prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

|                     |   |
|---------------------|---|
| Article Number      | 133-02353   |
| Type                | FTOVALSTRNRLF   |
| Color               | Black (BK)  |
| Quantity Per        | carton  |
| Product Description | Designed for use with cable ties or electrical tape, bundling clips provide a simple method of securing wire and cable bundles. HellermannTyton offers these clips in standard and standoff orientations, with a variety of mounting options. |
| Short Description   | Angled Bundling Clip, 65mm Long, 0.60 - 6.75mm Panel Thickness, PA66HIRHSUV, Black, 4000/ctn  |
| Global Part Name    | FTOVALSTRNRLF-PA66HIRHSUV-BK  |

|                                     |  |
|-------------------------------------|--|
| Length L (Imperial)                 | 2.55   |
| Length L (Metric)                   | 64.7   |
| Fixation Method                     | Fir Tree   |
| Height H (Imperial)                 | 0.89   |
| Height H (Metric)                   | 22.6   |
| Panel Thickness Min (Imperial)      | 0.02   |
| Panel Thickness Max (Imperial)      | 0.27   |
| Panel Thickness Min (Metric)        | 0.6  |
| Panel Thickness Max (Metric)        | 6.75   |
| Mounting Hole Diameter D (Imperial) | 0.26" x 0.47   |
| Mounting Hole Diameter D (Metric)   | 6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 12.5 mm                  |
| Material                            | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut                   | PA66HIRHSUV  |
| Flammability                        | UL 94 HB   |
| Halogen Free                        | Yes  |

|                              |                                   |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No)        | Yes                               |
| Operating Temperature        | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 4000                              |
| Package Quantity (Metric)    | 4000                              |
| Customs Number               | 3926909988                        |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)