

# Push-in T-connector NPQP-T-Q10-E-FD-P10

Part number: 133113

**FESTO**



## Data sheet

| Feature                                  | Value   |
|--|---|
| Size                                     | Standard                                      |
| Nominal width                            | 8.1 mm  |
| Design                                   | T-shape                                       |
| Pack size                                | 10  |
| Structural design                        | Push-pull principle                           |
| Temperature-dependent operating pressure | -0.95 bar ... 10 bar                          |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Information on operating and pilot media | Operation with oil lubrication possible       |
| Corrosion resistance class (CRC)         | 4 - Particularly high corrosion stress        |
| LABS (PWIS) conformity                   | VDMA24364 zone III                            |
| For use in the food industry             | See supplementary material information        |
| Ambient temperature                      | -20 °C ... 60 °C                              |
| Product weight                           | 21 g  |
| Pneumatic connection 1                   | for pneumatic tubing outside diameter 10 mm   |
| Pneumatic connection 2                   | for pneumatic tubing outside diameter 10 mm   |
| Note on materials                        | RoHS-compliant                                |
| Housing material                         | PP  |
| Material of tube retaining claw          | High-alloy stainless steel                    |