SIEMENS

Data sheet



Illuminated pushbutton, 22 mm, round, plastic, blue, pushbutton, flat momentary contact type, with laser labeling, upper case

product brand name	SIRIUS ACT
product designation	Illuminated pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Plastic, black, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Flat button
principle of operation of the actuating element	momentary contact type
product extension optional	
• light source	Yes
contact module	Yes
color of the actuating element	blue
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	29.5 mm
marking of the actuating element	Any inscription, text in upper case
Front ring	
	N/
product component front ring	Yes
design of the front ring	Yes Standard
design of the front ring	Standard
design of the front ring material of the front ring	Standard plastic
design of the front ring material of the front ring color of the front ring	Standard plastic
design of the front ring material of the front ring color of the front ring General technical data	Standard plastic black
design of the front ring material of the front ring color of the front ring General technical data protection class IP	Standard plastic black IP66, IP67, IP69(IP69K)
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating	Standard plastic black IP66, IP67, IP69(IP69K)
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 operating frequency maximum	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 operating frequency maximum mechanical service life (switching cycles) typical	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h 3 000 000
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 operating frequency maximum	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 operating frequency maximum mechanical service life (switching cycles) typical	Standard plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h 3 000 000

 ambient temperature during storage 	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	11 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AB50-0AA0-Z Y11

Cax online generator

 $\underline{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1001-0AB50-0AA0-Z\ Y11001-0AB50-0AA0-Z\ Y11001-0AA0-Z\ Y11001-0AA0-Z\ Y11001-0AA0-Z\ Y11001-0AA0-Z\ Y11001-0AA0-Z\ Y11001-0AA0-Z\ Y11001$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AB50-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AB50-0AA0-Z Y11&lang=en

last modified: 12/21/2020 🖸