

# Lighting Controls

DATE: \_\_\_\_\_ LOCATION: \_\_\_\_\_

TYPE: \_\_\_\_\_ PROJECT: \_\_\_\_\_

CATALOG #: \_\_\_\_\_

## OMNI® LINE VOLTAGE ULTRASONIC CEILING SENSOR

CEILING MOUNT OCCUPANCY SENSORS

### FEATURES

- IntelliDAPT® self-adaptive technology — no manual adjustment required
- Superior all-digital ultrasonic (US) minor motion detection
- Non-volatile memory for sensor settings
- 500–2,000 square-foot coverage area (depending on model)
- Self-contained power supply
- Universal voltage (100–277VAC; 50/60 Hz)
- UL and cUL listed
- Five-year warranty



### SPECIFICATIONS

#### CONSTRUCTION

- Casing- rugged, high-impact, injection-molded plastic KJB ABS
- Cicolac (UL-945VA) flame class rating, UV inhibitors
- Color-coded leads are 6" long (152.4 mm)
- 8.2 oz.
- Off-white
- Green - ultrasonic motion

#### MOUNTING

- Mounting using a 3 inch (76.2mm) mud ring attached to 4 inch (101.6mm) square electrical box
- Recommended MAX mounting height: 12ft. (3.66m)

#### ELECTRICAL

- OMNIUS500: 40kHz output OMNIUS2000: 32kHz output
- 100-277VAC; 50/60Hz

#### ELECTRICAL (CONTINUED)

- 20A: 120VAC Incandescent
- 20A: 120 or 277VAC Magnetic Ballast
- 16A: 120 or 277VAC Electronic Ballast
- 1HP: 120VAC Motor Load
- 1HP: 277VAC Motor Load

#### OPERATIONS

- IntelliDAPT
  - Auto reset from test setting
  - Self-adjusting timer
  - Self-adjusting ultrasonic thresholds
  - Automatic false-ON/false-OFF corrections
- Coverage
  - 500–2,000 square feet (depending on model)

#### OPERATIONS (CONTINUED)

- Timer Settings
  - Automatic mode: 8–30 min. (self-adjusts based on occupancy)
  - Test mode: 8 seconds (for an easy check at installation)

#### OPERATING ENVIRONMENT

- Indoor use only
- Operating temperature: 32° to 104°F (0° to 40°C)
- Relative humidity (non-condensing): 0% to 95%

#### CERTIFICATIONS

- UL and cUL listed

#### WARRANTY

- 5 year warranty

### ORDERING GUIDE

Example: OMNIUS500BP1277

CATALOG #

#### Series

- OMNIUS500BP1277 Line Voltage Ultrasonic Ceiling Sensor 500 sq. ft. coverage
- OMNIUS2000BP1277 Line Voltage Ultrasonic Ceiling Sensor 2000 sq. ft. coverage

# Lighting Controls


DATE: \_\_\_\_\_ LOCATION: \_\_\_\_\_

TYPE: \_\_\_\_\_ PROJECT: \_\_\_\_\_

CATALOG #: \_\_\_\_\_

## OMNI® LINE VOLTAGE ULTRASONIC CEILING SENSOR CEILING MOUNT OCCUPANCY SENSORS


### DIMENSIONS



### ADDITIONAL INFORMATION


#### Coverage Patterns

US 500 Range



Minor Motion  
Major Motion

US 2000 Range



Minor Motion  
Major Motion

# Lighting Controls

## OMNI® LINE VOLTAGE ULTRASONIC CEILING SENSOR CEILING MOUNT OCCUPANCY SENSORS

### ADDITIONAL INFORMATION (CONTINUED)

#### Wiring Diagram

