



Quality Products. Service Excellence.

## Type 12 Mild Steel Pushbutton Enclosures *1435 Series*



### Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and water.

### Standards

- UL 508A Type 12 and 13
- CSA Type 12 and 13
- **Complies with**
  - NEMA Type 12 and 13
  - IEC 60529, IP54
- Appropriate components are required to maintain these standards.

### Construction

- Formed 14 gauge steel except A and B which are 16 gauge.
- Smooth continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Captive cover screws thread into sealed wells.
- Larger enclosures provide internally hinged removable covers, designed to hold the cover open during wiring (see table).
- Oil resistant gasket and adhesive.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure.

### Finish

- Cover and enclosure are phosphatized and finished in ANSI 61 gray powder coating.

### Accessories

- Hole Plugs
- Pedestal and Base
- General Accessories

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

30.5mm PB Part No.	22.5mm PB Part No.	No. of Holes	H	Enclosure	
				W	D
1435A <sup>1</sup>	1435MA <sup>1</sup>	1	3.50	3.25	2.75
1435B <sup>1</sup>	1435MB <sup>1</sup>	2	5.75	3.25	2.75
1435C <sup>1</sup>	1435MC <sup>1</sup>	3	8.00	3.25	2.75

30.5mm PB Part No.	22.5mm PB Part No.	No. of Holes	Enclosure		
			H	W	D
1435D <sup>1</sup>	1435MD <sup>1</sup>	4	10.25	3.25	2.75
1435F	1435MF	4	7.25	6.25	3.00
1435H	1435MH	6	9.50	6.25	3.00
1435K	1435MK	9	9.50	8.50	3.00
1435O	1435MO	12	11.75	8.50	3.00
1435S	1435MS	16	11.75	10.75	3.00

<sup>1</sup> Not hinged

Tags: **pushbutton, Type 12, button, dial, switch, pilot light, heavy duty**

*Data subject to change without notice*

© 2023. Hammond Manufacturing Ltd. All rights reserved.