

FLORENTINA-HLD-RS

~10° real spot beam

SPECIFICATION:

Dimensions	285.6 x 19.5 mm
Height	9.5 mm
Fastening	clips
ROHS compliant	yes ⓘ

MATERIALS:

Component	Type	Material	Colour	Finish
TINA2-RS	Single lens	PMMA	clear	
FLORENTINA-HLD	Holder	PC	black	

ORDERING INFORMATION:


Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CP14866_FLORENTINA-HLD-RS » Box size: 398 x 298 x 140 mm	Single lens	160	32	16	5.2




OPTICAL RESULTS (MEASURED):





LED QUICK FLUX LED FL-XG 1x12 xxx
FWHM / FWTM 18.0° / 35.0°
Efficiency 84 %
Peak intensity 6.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14446_FLORENTINA-SHD





LED XP-E2
FWHM / FWTM 11.0° / 21.0°
Efficiency 84 %
Peak intensity 16.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14446_FLORENTINA-SHD



LED XP-G2
FWHM / FWTM 15.0° / 28.0°
Efficiency 86 %
Peak intensity 9.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14446_FLORENTINA-SHD




LED XP-G3
FWHM / FWTM 18.0° / 35.0°
Efficiency 84 %
Peak intensity 6.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14446_FLORENTINA-SHD



OPTICAL RESULTS (MEASURED):


LUMILEDS

LED LUXEON Rebel ES
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 82 %
 Peak intensity 7.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD





LUMILEDS

LED LUXEON Rebel Plus
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 82 %
 Peak intensity 11.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD




LUMILEDS

LED LUXEON TX
 FWHM / FWTM 15.0° / 30.0°
 Efficiency 83 %
 Peak intensity 8.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD











LUMILEDS

LED LUXEON Z ES
 FWHM / FWTM 13.0° / 24.0°
 Efficiency 84 %
 Peak intensity 14.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD



OPTICAL RESULTS (MEASURED):


<p>NICHIA</p> <p>LED NCSxx19B FWHM / FWTM 13.0° / 28.0° Efficiency 80 % Peak intensity 10.3 cd/lm LEDs/each optic 1 Light colour White Required components: C14446_FLORENTINA-SHD</p>		
<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM / FWTM 16.0° / 34.0° Efficiency 79 % Peak intensity 6.7 cd/lm LEDs/each optic 1 Light colour White Required components: C14446_FLORENTINA-SHD</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLON Square EC FWHM / FWTM 15.0° / 28.0° Efficiency 81 % Peak intensity 9 cd/lm LEDs/each optic 1 Light colour White Required components: C14446_FLORENTINA-SHD</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLON Square EC FWHM / FWTM 15.0° / 28.0° Efficiency 81 % Peak intensity 9 cd/lm LEDs/each optic 1 Light colour White Required components: C14446_FLORENTINA-SHD</p>		

OPTICAL RESULTS (MEASURED):

OSRAM

Opto Semiconductors


LED OSLOM SSL 150
 FWHM / FWTM 11.0° / 21.0°
 Efficiency 82 %
 Peak intensity 17.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD



OSRAM

Opto Semiconductors



LED OSLOM SSL 150
 FWHM / FWTM 11.0° / 22.0°
 Efficiency 84 %
 Peak intensity 15.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OSRAM



Opto Semiconductors

LED OSLOM SSL 80
 FWHM / FWTM 15.0° / 28.0°
 Efficiency 82 %
 Peak intensity 9.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD



SAMSUNG

LED LH351B
 FWHM / FWTM 18.0° / 33.0°
 Efficiency 84 %
 Peak intensity 6.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14446_FLORENTINA-SHD




OPTICAL RESULTS (MEASURED):





TOSHIBA

Leading Innovation >>>

LED TL1L4
FWHM / FWTM 16.0° / 33.0°
Efficiency 82 %
Peak intensity 7.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14446_FLORENTINA-SHD



OPTICAL RESULTS (SIMULATED):

<p>CREE LEDs</p> <p>LED J Series 3030 FWHM / FWTM 16.0° / 32.0° Efficiency 91 % Peak intensity 8.2 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>CREE LEDs</p> <p>LED J Series 3030 FWHM / FWTM 16.0° / 32.0° Efficiency 88 % Peak intensity 8.4 cd/lm LEDs/each optic 1 Light colour White Required components: C14446_FLORENTINA-SHD</p>	
<p>CREE LEDs</p> <p>LED XB-D FWHM / FWTM 12.0° / 26.0° Efficiency 90 % Peak intensity 13.3 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>CREE LEDs</p> <p>LED XD16 FWHM / FWTM 12.0° / 24.0° Efficiency 89 % Peak intensity 13.1 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	

OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED: NCSxE17A FWHM / FWTM: 11.0° / 22.0° Efficiency: 88 % Peak intensity: 22.4 cd/lm LEDs/each optic: 1 Light colour: White Required components: C14446_FLORENTINA-SHD</p>	
<p>NICHIA</p> <p>LED: NVSU119C FWHM / FWTM: 16.0° / 30.0° Efficiency: 92 % LEDs/each optic: 1 Light colour: UV-A Required components:</p>	
<p>NICHIA</p> <p>LED: NVSxE21A FWHM / FWTM: 13.0° / 26.0° Efficiency: 88 % Peak intensity: 14.7 cd/lm LEDs/each optic: 1 Light colour: White Required components: C14446_FLORENTINA-SHD</p>	
<p>NICHIA</p> <p>LED: NWSx229A FWHM / FWTM: 24.0° / 44.0° Efficiency: 86 % Peak intensity: 4 cd/lm LEDs/each optic: 1 Light colour: White Required components: C14446_FLORENTINA-SHD</p>	

OPTICAL RESULTS (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)