


Specification Sheet

Part Number: 151-00651



The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

Bundling Clip with Fir Tree, 1.5" Long, 0.7 - 18.0mm Panel Thickness, PA66HIRHS, Natural, 2000/box

Article Number 151-00651

Type TC6FT6LG

Color Natural (NA)

Quantity Per box

Product Description HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties.

Short Description Bundling Clip with Fir Tree, 1.5" Long, 0.7 - 18.0mm Panel Thickness, PA66HIRHS, Natural, 2000/box

Global Part Name TC6FT6LG-PA66HIRHS-NA

| | |
|---|--------------|
| Length L (Imperial) | 1.5 |
| Length L (Metric) | 38.1 |
| Fixation Method | Fir Tree |
| Width W (Imperial) | 0.5 |
| Width W (Metric) | 12.0 |
| Height H (Imperial) | 1.0 |
| Height H (Metric) | 26.60 |
| Panel Thickness Min (Imperial) | 0.03 |
| Panel Thickness Max (Imperial) | 0.71 |
| Panel Thickness Min (Metric) | 0.70 |
| Panel Thickness Max (Metric) | 18.0 |
| Mounting Hole Diameter D (Imperial) | 0.26 |
| Mounting Hole Diameter D (Metric) | 6.2 - 6.8 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Metric) | 6.2 |

| | |
|------------------------------|--|
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 2000 |
| Package Quantity (Metric) | 2000 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)