

## Specification Sheet

Part Number: 151-01611

Easy to install, remove and reposition with just a quarter-turn – no tools necessary.

Multi-directional cable tie slot allows for routing a bundle parallel to or perpendicular to the frame.

Low profile is ideal for cramped spaces.

Designed to fit an 80/20 profile with a T-slot of 8 mm (0.32") and external dimensions of 40 mm (1.5").



Aluminum Frame Mount for 40mm Frame, 2.5 - 3.0mm Panel Thickness, PA66, White, 100/bg

Article Number 151-01611

Type AFLM30-1

Color Natural (NA)

Quantity Per bag

Product Description Aluminum frame mounts can be used with 20, 30 or 40 mm square frames from the major aluminum frame manufacturers. As there is no need to screw them in place, these mounts offer maximum ease of use and fast installation.

Short Description Aluminum Frame Mount for 40mm Frame, 2.5 - 3.0mm Panel Thickness, PA66, White, 100/bg

Global Part Name AFLM30-1-PA66-NA

Length L (Imperial) 1.02

Length L (Metric) 26.0

Width W (Imperial) 0.71

Width W (Metric) 18

Cable Ties T18 - T50

Height H (Imperial) 0.68

Height H (Metric) 17.2

Cable Tie Width Max (Imperial) 0.45

Cable Tie Width Max (Metric) 11.5

Panel Thickness Min (Imperial) 0.10

Panel Thickness Max (Imperial) 0.12

Panel Thickness Min (Metric) 2.5

Panel Thickness Max (Metric) 3.0

Material Polyamide 6.6 (PA66)

Material Shortcut	PA66
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)