


Specification Sheet

Part Number: 151-03254



Separates and secures bundles avoiding abrasion.

Designed to handle both convoluted tubing and bundles not covered in convoluted tubing.

Come in a variety of sizes and colors to be easily identified.

HDCM2 Clamp Bundle Separator, Two Hole, PA66HIRGF15, Green, 600/pkg

Article Number 151-03254

Type HDCM2B

Color Green (GN)

Quantity Per bag

Product Description HC Clamps separate multiple bundles and secure them to brackets or frame rails. Each mount has two pawls for easy pre-installation on a threaded fastener prior to securing with a mechanical fastener. HC Clamps have ribs that make them ideal for convoluted tubing, but they can also be used to separate separate bundles that aren't protected with convoluted tubing.

Short Description HDCM2 Clamp Bundle Separator, Two Hole, PA66HIRGF15, Green, 600/pkg

Global Part Name HDCM2B-PA66GF15-GN

Length L (Imperial) 2.72

Length L (Metric) 69.1

Variant Separators

Width W (Imperial) 1.12

Width W (Metric) 28.48

Bundle Diameter Min (Imperial) 0.677

Bundle Diameter Min (Metric) 17.20

Bundle Diameter Max (Imperial) 0.677

Bundle Diameter Max (Metric) 17.20

Bundle Diameter 1st Loop Max (Imperial) 0.677

Bundle Diameter 1st Loop Max (Metric) 17.20

Bundle Diameter 2nd Loop Max (Imperial) 0.677

Bundle Diameter 2nd Loop Max (Metric) 17.20

Height H (Imperial) 1.34

Height H (Metric) 34

Mounting Hole Diameter D (Imperial)	0.32
Mounting Hole Diameter D (Metric)	8.2 mm
Mounting Hole Diameter D Min (Imperial)	0.32
Mounting Hole Diameter D Max (Imperial)	0.32
Mounting Hole Diameter D Max (Metric)	8.2

Material Polyamide 6.6 glass fiber reinforced (PA66GF15%)

Material Shortcut PA66GF15

UV Resistant (Yes/No) No

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 600

Package Quantity (Metric) 600

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)