

Specification Sheet

Part Number: MB5A10C2


For use with HellermannTyton T18 - T150 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 2.1 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 1.49" x 1.49", Use With T18-T150 Cable Tie, PA66, White, 100/pkg

Article Number 151-28529

Type MB5A

Color White (WH)

Quantity Per bag

Product Description MB5A adhesive mounts are for use with HellermannTyton T18 - T150 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.

Short Description Rubber Adhesive Cable Tie Mount, 1.49" x 1.49", Use With T18-T150 Cable Tie, PA66, White, 100/pkg

| | |
|---------------------------------------|-----------------------------|
| Global Part Name | MB5A-PA66-WH |
| Length L (Imperial) | 1.49 |
| Length L (Metric) | 37.7 |
| Fixation Method | Screw Mounting and Adhesive |
| Width W (Imperial) | 1.49 |
| Width W (Metric) | 37.7 |
| Cable Ties | T18 - T150 |
| Height H (Imperial) | .28 |
| Height H (Metric) | 7.1 |
| Cable Tie Width Max (Imperial) | 0.35 |
| Cable Tie Width Max (Metric) | 8.9 |
| Mounting Hole Diameter D (Imperial) | 0.19 |
| Mounting Hole Diameter D (Metric) | 4.8 mm |
| Mounting Hole Diameter D Max (Metric) | 4.8 |
| Mounting Hole Centers (Imperial) | 1.0 |

| | |
|--------------------------------|---|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Adhesive | Synthetic rubber with base of polyethylene foam |
| Flammability | UL 94 V-2 (excluding adhesive) |
| UV Resistant (Yes/No) | No |
| Adhesive Operating Temperature | 0°F to +150°F (-18 °C to +66 °C) |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

