

Specification Sheet

Part Number: CTAP210C2



Mount provides a "stand-off" for perpendicular bundles. Secures with a single screw with the option of an additional screw, providing extra stability.

Cable Tie Anchor Mount, 0.20 x.70" Hole Dia, 0.20" Max Tie Width, PA66, White, 100/pkg

Article Number 151-30200

Type CTAP2

Color White (WH)

Quantity Per bag

Product Description HellermannTyton cable tie anchor plates are designed as a "stand-off" mount for perpendicular wire bundles. These mounts offer an elongated mounting hole for easier alignment of wire bundles. The mounts are installed quick and easy by securing a single screw, with the option of an additional screw for maximum stability.

Short Description Cable Tie Anchor Mount, 0.20 x.70" Hole Dia, 0.20" Max Tie Width, PA66, White, 100/pkg

Global Part Name CTAP2-PA66-WH

Length L (Imperial)	2.13
Length L (Metric)	54.1
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.5
Width W (Metric)	12.7
Cable Ties	T18 - T50
Height H (Imperial)	.14
Height H (Metric)	3.50
Cable Tie Width Max (Imperial)	0.2
Cable Tie Width Max (Metric)	5.0
Mounting Hole Diameter D (Imperial)	0.2 x 0.7
Mounting Hole Diameter D (Metric)	5.0 x 19.0 mm
Mounting Hole Diameter D Max (Metric)	19.0
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66

Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	UL-ZODZ2.E64139
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

