

Pre-assembled relay module PRS..., Screw connection, Consisting of: relay socket base, power contact relay, pluggable display/suppression module and holding clip, 2 CO contacts, Input voltage: 24 VAC

Kaufmännische Daten

Artikelnummer	15166.2
Artikelbezeichnung	PRSU 2/24V AC
GTIN (EAN)	4044211046453
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	52.7 g
Weight per piece (including packaging)	58.8 g
Unit of weight	G
Customs number	85364900
Country of origin	CN
Product description	Complete module

### Technische Daten

#### Dimensions

Length	76 mm
Width	15.6 mm
Height TS 35 / 7.5 with BA	71 mm

#### Ratings

Rated voltage Un	24 VAC -
Overvoltage category	III
Contamination degree	3

#### Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	2.5 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	1.5 mm <sup>2</sup>
Stripping length	8 mm
Torque	0.8 Nm

#### Input data

Drop-out voltage	3,6 VAC
Operating range	ab 18 VAC
Power consumption	0,75 W

#### Output data

Switching voltage / switching voltage max.	250 / 400 VAC
Continuous current max. / Inrush current max.	8 / 15 A
Contact configuration	2 CO contacts
Switching capacity, max.	2000 VA
Electrical lifespan (AC1)	1x10 <sup>5</sup>
Mechanical lifespan	2x10 <sup>6</sup>
Bounce time at close of the NO/NC contact	6/8 ms

### Technische Daten

#### Materials

Contact material	AgNi 90/10
Flammability class UL 94	V-0
Working temperature, min.	-25 °C
Working temperature, max.	80 °C

#### Further technical data

Degree of protection	IP20
Status display	✓
Insulation voltage coil/contact	5 kV
Response/release time	7 / 2 ms
Insulation voltage contact/contact	1 kV
Vibration resistance NO/NC	20/5 g
Pinning	5 mm

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Zulassungen


Standards and regulations

CE compliant	yes
--------------	-----

---

### Medien

---



### Zubehör

#### Cross-connector



External cross-connector insulated, for relay socket base PRS 1 and PRS 2/6-pole, can be shortened, Voltage: 250 V, Current 10 A

Artikelnummer	Artikelbezeichnung	GTIN (EAN)	VPE
<u>15779.2</u>	AQI/PRS/8 BK	4044211134006	20 ST


#### Screwdriver



Screwdriver with bare blade, Colour: Black-grey

Artikelnummer	Artikelbezeichnung	GTIN (EAN)	VPE
<u>1086.0</u>	SDB 0,6x3,5	4044211014797	1 ST

#### Relays



Plug-in miniature power relay, Encapsulated design with power contact, 2 CO contacts, Input voltage: 24 VAC

Artikelnummer	Artikelbezeichnung	GTIN (EAN)	VPE
<u>6484.2</u>	PRS 2/24V AC	4044211074234	1 ST

#### Holding clamp



Relay holding clip, With eject, Suitable for relay socket base PRS 1 and PRS 2, for miniature power relays

Artikelnummer	Artikelbezeichnung	GTIN (EAN)	VPE
<u>15138.2</u>	PRS C1/2	4044211046217	1 ST

#### Insert modules

Datenblatt

15166.2 PRSU 2/24V AC



Insertion module, Suitable for relay socket base PRS, LED red status display

Artikelnummer	Artikelbezeichnung	GTIN (EAN)	VPE
<u>15175.2</u>	PRS LED(RD) 24V UC	4044211046521	1 ST