

# Blanking plug QSC-6H

Part number: 153268

FESTO



## Data sheet

| Feature   | Value  |
|---|--|
| Size  | Standard   |
| Mounting position                               | Any  |
| Design  | Blanking plug  |
| Pack size                                       | 10   |
| Operating pressure for entire temperature range | -0.095 MPa ... 0.6 MPa   |
| Operating pressure for entire temperature range | -0.95 bar ... 6 bar  |
| Operating pressure for entire temperature range | -13.775 psi ... 87 psi   |
| Temperature-dependent operating pressure        | -0.095 MPa ... 1.4 MPa   |
| Temperature-dependent operating pressure        | -0.95 bar ... 14 bar   |
| Temperature-dependent operating pressure        | -13.775 psi ... 203 psi  |
| Maritime classification                         | See certificate  |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-]<br>Water as per manufacturer's declaration at <a href="http://www.festo.com">www.festo.com</a> |
| Information on operating and pilot media        | Operation with oil lubrication possible  |
| Corrosion resistance class (CRC)                | 1 - Low corrosion stress   |
| LABS (PWIS) conformity                          | VDMA24364-B1/B2-L  |
| Ambient temperature                             | -10 °C ... 80 °C   |
| Product weight                                  | 0.5 g  |
| Pneumatic connection 1                          | Push-in sleeve Ø 6 mm  |
| Note on materials                               | RoHS-compliant   |
| Housing material                                | PBT  |