

Specification Sheet

Part Number: 156-03002

Clamp and mount combination means no extra hardware is needed, for time-saving, toolless, one-handed installation.

Three size ranges handle diameters from 0.5" to 2", reducing part inventory.

Clamp saddle provides additional attachment option using a cable tie.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.



Quick2Clamp, 0.76" - 1.42" Bundle Dia, 1-5/8" Strut Attachment, PA66HIRHSUV, Black, 200/box

Article Number 156-03002

Type IRCCSTRUT

Color Black (BK)

Quantity Per carton

Product Description The Quick2Clamp offers ultra-fast installation and versatility for

managing conduit, tubing and cables. The built-in strut mount attaches with a simple twist. The one-piece design makes it simple to install without tools. Robust, adjustable clamp closes by hand to the desired diameter. A release feature allows easy and nondestructive maintenance simply by using a flat-head screwdriver. In this way, the

clamp can be reused or serviced without removing it from the strut.

| Short Description | Quick2Clamp, 0.76" - 1.42" Bundle Dia, 1-5/8" Strut Attachment, PA66HIRHSUV, Black, 200/box | | |
|--------------------------------|---|--|--|
| Global Part Name | IRCCSTRUT-PA66HIRHSUV-BK | | |
| | | | |
| Length L (Imperial) | 4.56 | | |
| Length L (Metric) | 115.9 | | |
| Fixation Method | 1-5/8 " Strut Attachment | | |
| Variant | Load Rating: 17 lbs, Safety Factor: 3 Pull Force Rating: 50 lbs | | |
| Width W (Imperial) | 1.37 | | |
| Width W (Metric) | 34.81 | | |
| Bundle Diameter Min (Imperial) | 0.76 | | |
| Bundle Diameter Min (Metric) | 19.4 | | |
| Bundle Diameter Max (Imperial) | 1.42 | | |
| Bundle Diameter Max (Metric) | 36.0 | | |
| Height H (Imperial) | 2.04 | | |
| Height H (Metric) | 51.8 | | |

Material Polyamide 6.6 high impact modified, heat and UV stabilized

(PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

UV Resistant (Yes/No) Yes

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Certification/Specification UL | UL2239 Conduit & Cable Hanger

UL Listed (US) Yes

Package Quantity (Imperial) 200

Package Quantity (Metric) 200

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).