

RONDA-WWW-C

~90° wide beam with holder C compatible with LEDiL HEKLA

SPECIFICATION:

Dimensions Ø 53.9 mm
Height 17 mm
Fastening socket
ROHS compliant yes ①



MATERIALS:

ComponentTypeMaterialColourFinishF15157_RONDA-WWWSingle lensPMMAclearF15635_RONDA-HLD-CHolderPCwhite

ORDERING INFORMATION:

Quantities for one set:

Single lens 1 Holder 1




Component		Qty in box	MOQ	MPQ	Box weight (kg)
F15157_RONDA-WWW » Box size: 480 x 280 x 300 mm	Single lens	420	120	30	6.3
F15635_RONDA-HLD-C » Box size: 480 x 280 x 300 mm	Holder	420	120	30	4.1

2/20




PRODUCT DATASHEET RONDA-WWW-C




See also our general installation guide: www.ledil.com/installation_guide

3/20




































Published: 09/07/2019

















PHILIPS

LED Fortimo SLM L09 CoB

FWHM / FWTM 81.0° / 120.0°
Efficiency 88 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White

Required components:

F15858_HEKLA-SOCKET-H



PHILIPS

LED Fortimo SLM L13 CoB

FWHM / FWTM 77.0° / 127.0°

Efficiency 82 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C16142_HEKLA-SOCKET-K Bender Wirth: 432 Typ L8




PHILIPS

LED Fortimo SLM L13 CoB

FWHM / FWTM 77.0° / 127.0°

Efficiency 82 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C16142_HEKLA-SOCKET-K Bender Wirth: 432 Typ L8




SAMSUNG

LED LC003D / LC006D / LC009D / LC013D

FWHM / FWTM 81.0° / 121.0°
Efficiency 90 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1

Light colour White Required components:

F15255_HEKLA-SOCKET-C





SAMSUNG LED LC010C FWHM/FWTM 94.0°/133.0°

Efficiency 89 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1

Light colour White
Required components:
F15848_HEKLA-SOCKET-G


SAMSUNG

LED LC010C G2 FWHM / FWTM 94.0° / 133.0°

Efficiency 89 %
Peak intensity 0.5 cd/m
LEDs/each optic 1
Light colour White

F15255_HEKLA-SOCKET-C

Required components:



SAMSUNG


LED LC010T (Tunable White)

FWHM / FWTM 76.0° / 117.0°
Efficiency 86 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1

Light colour Tunable White

Required components:


C16142_HEKLA-SOCKET-K Bender Wirth: 501 Typ L8



SAMSUNG


LED LC016D / LC019D / LC026D / LC033D

FWHM / FWTM 80.0° / 131.0°
Efficiency 82 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15859_HEKLA-SOCKET-I




Published: 09/07/2019
















OPTICAL RESULTS (SIMULATED):




LED MJT COB LES 14.5

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 79.0° / 133.0° Efficiency 73 % Peak intensity 0.4 cd/lm

LEDs/each optic Light colour White

Required components: F17438_HEKLA-G2-I




SEOUL SEOUL SEMICONDUCTOR

MJT COB LES 6 LED

FWHM / FWTM 85.0° / 116.0° Efficiency 84 % Peak intensity 0.5 cd/lm LEDs/each optic 1

White Light colour

Required components: F17435_HEKLA-G2-C




SEOUL

LED MJT COB LES 9.8

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 80.0° / 117.0° Efficiency 83 % 0.5 cd/lm

Peak intensity LEDs/each optic 1 Light colour White Required components:

F17435_HEKLA-G2-C





PRODUCT DATASHEET RONDA-WWW-C

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

20/20

www.ledil.com/ where_to_buy