



Main

| | |
|-------------------------------|--------------------|
| Range of Product | Harmony XAC |
| Product or Component Type | Contact block |
| Component name | ZB2 |
| Electrical circuit type | Control circuit |
| Contact block application | Single speed |
| Contact block type | Single |
| Type of operator | Spring return |
| Product Compatibility | XACA XB4 XB5 |
| Contacts type and composition | 1 NC |
| Mounting of block | Front mounting |
| Contact operation | Slow-break |

Complementary

| | |
|---|---|
| Connections - terminals | Screw clamps terminals, 1 x 2.5 mm ² with or without cable end Screw clamps terminals, 2 x 1.5 mm ² with or without cable end |
| Mechanical durability | 1000000 cycles |
| Contact code designation | A600 AC-15, U _e = 240 V, I _e = 3 A IEC 947-5-1 appendix A A600 AC-15, U _e = 600 V, I _e = 1.2 A IEC 947-5-1 appendix A Q600 DC-13, U _e = 250 V, I _e = 0.27 A IEC 947-5-1 appendix A Q600 DC-13, U _e = 600 V, I _e = 0.1 A IEC 947-5-1 appendix A |
| [I _{th} e] conventional enclosed thermal current | 10 A |
| [U _i] rated insulation voltage | 600 V 3)IEC 60947-1 |
| [U _{imp}] rated impulse withstand voltage | 6 kV IEC 60947-1 |
| Maximum resistance across terminals | 25 MOhm |
| Operating force | 13...15 N |
| Short-circuit protection | 10 A fuse protection cartridge gG (gl) |
| Rated operational power in W | 40 W DC-13 1000000 cycles 3600 cyc/h 120 V 0.5 IEC 60947-5-1 48 W DC-13 1000000 cycles 3600 cyc/h 48 V 0.5 IEC 60947-5-1 65 W DC-13 1000000 cycles 3600 cyc/h 24 V 0.5 IEC 60947-5-1 |
| Terminals description ISO n°1 | (11-12)NC |
| Net Weight | 0.04 lb(US) (0.02 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60204-32 EN/IEC 60947-5-1 CSA C22.2 No 14 UL 508 |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn 10...500 Hz)IEC 60068-2-6 |
| Shock resistance | 100 gn IEC 60068-2-27 |
| Electrical shock protection class | Class II IEC 61140 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 22466 - PUSHBUTTON, ACCESSORIES |
| Discount Schedule | CS2 |
| GTIN | 3389110612615 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.56 oz (16 g) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-----------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.79 in (2 cm) |
| Package 1 width | 5.91 in (15 cm) |
| Package 1 Length | 5.12 in (13 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|