## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90783

Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability. True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits.

All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.

PA66 nylon material has high resistance to salts, oils, weak acids, and solvents.

Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.



HelaGuard Non-Metallic Ultra IP68 Fitting, Straight, 0.50" NPT Thread, 0.50" Dia., PA66, Black, 1/pkg

Article Number 166-90783

Type HGU050-S-0500

Color Black (BK)

Quantity Per pack

| Product Description            | Straight Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection. |
|--------------------------------|---|
| Short Description              | HelaGuard Non-Metallic Ultra IP68 Fitting, Straight, 0.50" NPT Thread, 0.50" Dia., PA66, Black, 1/pkg   |
| Global Part Name               | HGU050-S-0500-PA66-BK   |
|                                |   |
| Length L (Imperial)            | 1.73  |
| Length L (Metric)              | 44  |
| Variant                        | Straight  |
| Outside Diameter OD (Imperial) | 1.26  |
| Outside Diameter OD (Metric)   | 32.0  |
| Nominal Diameter (Imperial)    | 0.5   |
| Nominal Diameter (Metric)      | 21  |
|                                |   |
|                                |   |
| Material                       | Polyamide 6.6 (PA66)  |
| Material Shortcut              | PA66  |

Yes

Halogen Free

| UV Resistant (Yes/No)        | No                                |
|------------------------------|-----------------------------------|
| Operating Temperature        | -58°F to +275°F (-50°C to +135°C) |
| Reach Compliant (Article 33) | No                                |
| ROHS Compliant               | Yes                               |
| UL Listed (US and Canada)    | Yes                               |
| UL Listed (US)               | Yes                               |
|                              |                                   |
| Package Quantity (Imperial)  | 1                                 |
| Package Quantity (Metric)    | 1                                 |
|                              |                                   |

## About HellermannTyton

**Customs Number** 

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (<a href="https://www.hellermann.tyton.com">www.hellermann.tyton.com</a>).

3926909988

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions