

## Housing - HC-B 48-TFL-96/O1PG36G - 1675175

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing, for single locking latch, height 96 mm, without screw connection, 1x Pg36, straight cable entry

The illustration shows version, panel mounting base with and without protective cover



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Weight per Piece (excluding packing) | 731.0 GRM |
| Custom tariff number                 | 85389099  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|        |          |
|--------|----------|
| Height | 96 mm    |
| Width  | 89 mm    |
| Length | 131.5 mm |

#### Ambient conditions

|                                      |                   |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65              |
| Ambient temperature (operation)      | -40 °C ... 125 °C |

#### General

|                      |                                      |
|----------------------|--------------------------------------|
| Note                 | For contact inserts HC-B48, DD216, M |
| Type                 | B48                                  |
| Housing type         | Sleeve housing                       |
| Locking type         | for single locking latch             |
| No. of cable outlets | 1                                    |
| Cable exit           | Straight                             |

# Housing - HC-B 48-TFL-96/O1PG36G - 1675175

## Technical data

### General

|                              |                     |
|------------------------------|---------------------|
| Screw connection             | none                |
| Type of the screw connection | 1x Pg36             |
| Housing material             | Aluminum die-cast   |
| Housing surface material     | Powder-coated, gray |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Approvals

### Approvals

---

Approvals

GOST

---

Ex Approvals

# Housing - HC-B 48-TFL-96/O1PG36G - 1675175


## Approvals

---

Approvals submitted

---

## Approval details



## Drawings

Dimensioned drawing

