

Specification Sheet

Part Number: 170-03078

Provides easy visual and safety identification of critical wiring components. Offers high tensile strength while maintaining extreme flexibility.

Expands up to 150% of flat diameter for easy installation.

Does not trap heat and humidity.

Installs quickly and accommodates expansions and varying cable assembly shapes, reducing installation costs.



Braided Sleeving, Expandable, 0.75" Dia, PET, Orange, 250 ft/bulk reel

Article Number 170-03078

Type BSP343B

Color Orange (OG), High Voltage (HV)

Quantity Per reel

Product Description Orange PET braided sleeving is an extremely flexible, general purpose

option for bundling and protecting wires and cables in abrasive type applications. Its color makes it ideal for systematic color coding of complex wiring installations. Commonly used to shield cable harnesses in battery powered vehicles, such as hybrid cars, golf carts and light

trucks.

Short Description Braided Sleeving, Expandable, 0.75" Dia, PET, Orange, 250 ft/bulk reel

OL-11	D	N.I
Global	Part	ivame

BSP343B-PET-OG

Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.5
Bundle Diameter Min (Metric)	12.7
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.8
Diameter D (Imperial)	0.75
Diameter D (Metric)	19.1
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	19.1
Material	Polyester (PET)
Material Shortcut	PET

UL 94 V-0 FMVSS 302 FAR 25

Halogen Free Yes

Flammability

Operating Temperature -94°F to +257°F (-70°C to +125°C)

No

Reach Compliant (Article 33) Yes

UV Resistant (Yes/No)

ROHS Compliant Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 250

Package Quantity (Metric) 76.20

Customs Number 5808100000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions