

STRADA-IP-2X6-VSM-PC

IESNA Type V (square) beam for wide area lighting such as car parks. Variant made from PC.

SPECIFICATION:

Dimensions	173.0 x 71.4 mm
Height	8 mm
Fastening	screw
Ingress protection classes	IP67
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish
STRADA-IP-2X6-VSM-PC	Multi-lens	PC	clear	
2X6-SEAL25	Seal	Silicone	white	

ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CS17082_STRADA-IP-2X6-VSM-PC » Box size: 476 x 273 x 247 mm	Multi-lens	120	40	40	6.8




See also our general installation guide: www.ledil.com/installation_guide









OPTICAL RESULTS (MEASURED):



LED	XP-G2
FWHM / FWTM	143.0° / 150.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




OPTICAL RESULTS (SIMULATED):

<p> bridgelux</p> <p>LED: Bridgelux SMD 5050 FWHM / FWTM: 146.0° / 159.0° Efficiency: 89 % Peak intensity: 0.3 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p> CREE LEDs</p> <p>LED: J Series 5050 Round LES FWHM / FWTM: 144.0 + 142.0° / 156.0 + 154.0° Efficiency: 90 % Peak intensity: 0.3 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p> CREE LEDs</p> <p>LED: J Series 5050B 30V K Class FWHM / FWTM: 146.0° / 160.0 + 159.0° Efficiency: 85 % Peak intensity: 0.3 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p> CREE LEDs</p> <p>LED: J Series 5050B 6V K Class FWHM / FWTM: 146.0 + 144.0° / 158.0 + 156.0° Efficiency: 90 % Peak intensity: 0.3 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	


OPTICAL RESULTS (SIMULATED):




LED XP-G3
 FWHM / FWTM 148.0° / 160.0°
 Efficiency 87 %
 Peak intensity 0.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED LUXEON 5050 Square LES
 FWHM / FWTM 145.0° / 158.0°
 Efficiency 90 %
 Peak intensity 0.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED LUXEON C
 FWHM / FWTM 152.0° / 167.0°
 Efficiency 84 %
 Peak intensity 0.3 cd/lm
 LEDs/each optic 4
 Light colour RGBW
 Required components:




LED NV4WB35AM
 FWHM / FWTM 145.0° / 154.0°
 Efficiency 90 %
 Peak intensity 0.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




OPTICAL RESULTS (SIMULATED):




LED NVSW219F
FWHM / FWTM 149.0° / 158.0°
Efficiency 89 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSW319B
FWHM / FWTM 151.0° / 160.0°
Efficiency 89 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19B/NVSxx19C
FWHM / FWTM 146.0° / 155.0°
Efficiency 89 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED PrevaLED Brick HP IP 2x6
FWHM / FWTM 146.0° / 155.0°
Efficiency 89 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):

OSRAM


Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3
 FWHM / FWTM 143.0° / 152.0°
 Efficiency 90 %
 Peak intensity 0.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LH351C
 FWHM / FWTM 148.0° / 156.0°
 Efficiency 90 %
 Peak intensity 0.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LH508A Plus
 FWHM / FWTM 144.0° / 158.0°
 Efficiency 89 %
 Peak intensity 0.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SEOUL SEMICONDUCTOR

LED Z5M3
 FWHM / FWTM 142.0° / 158.0°
 Efficiency 89 %
 Peak intensity 0.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)