



Note

- ① - Contact livré non assemblé
Contact delivered unassembled
- ② - Cable compatible: Belden 1855A
Cable compatible: Belden 1855A
- ③ - Outil de sertissage:
Contact intérieur M22520/2-01 avec positionneur M22520/2-35(5)
Contact extérieur M22520/5-01 avec positionneur M22520/5-05B
- ④ - Crimping tool:
Inner contact M22520/2-01 with positioner M22520/2-35(5)
Outer contact M22520/5-01 with positioner M22520/5-05B
- ⑤ - Matières:
- Contact extérieur: inox
- Contact intermédiaire: alliage de cuivre
- Contact intérieur, fut de sertissage et ferule: laiton
- Isolants: PTFE ou équivalent
Material
- Outer contact: Stainless steel
- Intermediary contact: copper alloy
- Inner contact, crimping barrel and ferrule: brass
- Inserts: PTFE or equivalent
- ⑥ - Traitements:
- Contact extérieur: passivation
- Contact intermédiaire, intérieur, fut de sertissage et ferrule: dorure
Finish
- Outer contact: passivation
- Intermediary and inner contact, crimping barrel and ferrule: Gold

| | | | |
|---|---------------------------|------------------------------|---|
| Douille coax T8 75 ohms 6G - SDI Socket coax S8 75 ohms 6G-SDI Ref: 612355 | | | |
| DRAWN BY: M.PRUD'HOM | | UPDATED BY: M.LAINE | |
| | | LAST APPROVED BY: L.LAGRANGE | |
| ALL DIMENSIONS ARE IN MM | AMPHENOL SOCAPEX | | ORIGINAL DRAWING DATE: 30/10/20 |
| SCALE: 7 | B.P. 29 74311 THYEZ CEDEX | | CONFIGURATION DATA ARE AVAILABLE IN PDM |
| | | REV: B | PAGE: 1/1 |
| 172-PLC-251-00 | | | |

IN THE CONSTANT PURPOSE OF IMPROVING ITS PRODUCTS, Amphenol Socapex RESERVES THE RIGHT TO MODIFY ANY DIMENSION OR CHARACTERISTICS.
FM.NPD.0036.THYZE.PUNE rev C