


**MSTB 2,5/ 6-G BK**

Order No.: 1756324

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1756324>

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: black, Assembly: Soldering

**Commercial data**

|                |  |
|----------------|--|
| GTIN (EAN)     | <br>4 017918 215699 |
| Note           | Made-to-order  |
| sales group    | E110   |
| Pack           | 50 pcs.  |
| Customs tariff | 85366990   |

**Product notes**WEEE/RoHS-compliant since:  
01/01/2003

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Certificates / Approvals**

Certification

CB, CSA, CUL, UL, VDE-PZI

**Accessories**

| Item            | Designation | Description   |
|-----------------|-------------|---|
| <b>Assembly</b> |             |   |
| 1759981         | MSTB-BF     | Mounting flange, for fixing both ends of the header onto the PCB, green insulating material, with M 2 x 14 screws and nuts. |
| 1755477         | MSTB-BL     | Keying cap, for forming sections, plugs onto header pin, green insulating material  |

|                |                       |   |
|----------------|-----------------------|---|
| <b>Marking</b> |                       |   |
| 1051993        | B-STIFT               | Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm   |
| 0804183        | SK 5/3,8:FORTL.ZAHLEN | Marker card, printed horizontally, self-adhesive, 12 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 120 terminal blocks                         |
| 0805072        | SK 5/3,8:SO           | Marker card, special printing, self-adhesive, labeled acc. to customer requirements, 12 identical marker strips per card, max. 25-position labeling per strip, color: white |
| 0805409        | SK 5/3,8:UNBEDRUCKT   | Marker cards, unprinted, with pitch divisions, self-adhesive, 10-section marker strips, 12 strips per card, can be labeled with the M-PEN                                   |

|                     |         |  |
|---------------------|---------|--|
| <b>Plug/Adapter</b> |         |  |
| 1734401             | CR-MSTB | Coding section, inserted into the recess in the header or the inverted plug, red insulating material |

**Additional products**

| Item            | Designation     | Description   |
|-----------------|-----------------|---|
| <b>Assembly</b> |                 |   |
| 1909252         | FKCT 2,5/ 6-ST  | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| <b>General</b>  |                 |   |
| 1910393         | FKC 2,5/ 6-ST   | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1909757         | FKCVR 2,5/ 6-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1910076         | FKCVW 2,5/ 6-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |

|         |                      |   |
|---------|----------------------|---|
| 1779453 | FRONT-MSTB 2,5/ 6-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1754520 | MSTB 2,5/ 6-ST       | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1765810 | MSTBP 2,5/ 6-ST      | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1779877 | MSTBT 2,5/ 6-ST      | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1792058 | MVSTBR 2,5/ 6-ST     | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1792566 | MVSTBW 2,5/ 6-ST     | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1768804 | SMSTB 2,5/ 6-ST      | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5 mm, Color: green, Metal surface: Sn |

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;