

Specification Sheet

Part Number: 181-31003

Strong fingers prevent unwanted breaking.

Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.

Restricted opening design in the finger of the duct helps keep wires in place.

Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

Supplied with mounting holes to streamline installation.

Optional covers enhance protection and appearance.



Slotted Wall Wiring Duct, 3" x 1", Non-Adhesive, PVC, Intrinsic Blue, 120ft/Carton

Article Number 181-31003

Type SL3X1

Color Intrinsic Blue (IBU)

Quantity Per carton

| Product Description | Manufactured from the same PVC material as standard Pro-Duct colors, HellermannTyton also offers an intrinsic blue color option. The intrinsic blue color indicates that the wiring contained in the duct runs to intrinsically safe components in the control panel. Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and Ts. |
|----------------------------------|--|
| Short Description | Slotted Wall Wiring Duct, 3" x 1", Non-Adhesive, PVC, Intrinsic Blue, 120ft/Carton |
| Global Part Name | SL3X1-PVC-BU |
| | |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 3.0 |
| Width W (Metric) | 76.2 |
| Height H (Imperial) | 1.06 |
| Height H (Metric) | 26.90 |
| Mounting Hole Centers (Imperial) | 4.0 |

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Halogen Free No UV Resistant (Yes/No) No **Operating Temperature** +122°F (+50°C) Reach Compliant (Article 33) No **ROHS Compliant** Yes Certification/Specification EN 50085-1:2005 + A1:2013 EN 50085-2-3 1A UL CSA UL Recognized (US) Yes Package Quantity (Imperial) 120.0 Package Quantity (Metric) 36.58

3925900000

About HellermannTyton

Customs Number

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.