

## **Specification Sheet**

Part Number: 181-91008

A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.

Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)



Wiring Duct Cover for 1" Duct, 6 ft Long, PVC, White, 120 ft/carton

Article Number 181-91008

Type TC1

Color White (WH)

Quantity Per carton

Product Description HellermannTyton's Pro-Duct wiring duct covers are sold separately and

interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers

are available in 6 foot lengths.

Short Description Wiring Duct Cover for 1" Duct, 6 ft Long, PVC, White, 120 ft/carton

Global	Dort	Nlama
CIUUAI	ган	manne

TC1-PVC-WH

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

1.0

Width W (Metric)

25.4

Height H (Imperial)

0.290

Height H (Metric)

7.36

Material

Polyvinylchloride (PVC)

**Material Shortcut** 

PVC

Flammability

UL 94 V-0

Halogen Free

No

UV Resistant (Yes/No)

No

**Operating Temperature** 

+122°F (+50°C)

Reach Compliant (Article 33)

No

**ROHS Compliant** 

Yes

Certification/Specification

UL CSA EN 50085-2-3\_1A EN 50085-1:2005 + A1:2013

UL Recognized (US)

Yes

Package Quantity (Imperial)

120.0

Package Quantity (Metric)

36.58

3925900000

## About HellermannTyton

**Customs Number** 

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (<a href="https://www.hellermann.tyton.com">www.hellermann.tyton.com</a>).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions