

Specification Sheet

Part Number: 184-11002

Narrow fingers reduce fanning of wires to terminal blocks, providing a neater appearance.

Each finger features a double restriction to hold wires in the bottom portion of the duct, simplifying installation.

Mounting holes are uniform in size to those in slotted and solid wall duct but are provided every two inches to accommodate compact designs and provide ease of installation.

Nonpermanent adhesive allows repositioning prior to final installation.



High Density Slotted Wall Wiring Duct, 1" x 1", Adhesive, PVC, White, 30ft/Box

Article Number 184-11002

Type SLHDA1X1

Color White (WH)

Quantity Per box

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features

narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and

components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" x 1", Adhesive, PVC, White,

30ft/Box

	_	
Global	Dart	Nama
เวเบเลเ	ran	ıvaııı ∈

SLHDA1X1-PVC-WH

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

1.0

Width W (Metric)

25.4

Height H (Imperial)

1.06

Height H (Metric)

26.9

Mounting Hole Centers (Imperial)

2.0

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Halogen Free

No

UV Resistant (Yes/No)

No

Operating Temperature

+122°F (+50°C)

Reach Compliant (Article 33)

No

ROHS Compliant

Yes

Certification/Specification	EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A CSA
UL Recognized (US)	Yes
Package Quantity (Imperial)	30.0
Package Quantity (Metric)	9.14
Customs Number	3925900000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions