

## **Specification Sheet**

Part Number: 184-24002



Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

High Density Slotted Wall Wiring Duct, 2" x 4", Adhesive, PVC, White, 30ft/Box

Article Number 184-24002

Type SLHDA2X4

Color White (WH)

Quantity Per box

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features

narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and

components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 2" x 4", Adhesive, PVC, White,

30ft/Box

| OL-11  | D    | N.I   |
|--------|------|-------|
| Global | Part | ivame |

SLHDA2X4-PVC-WH

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

2.0

Width W (Metric)

50.8

Height H (Imperial)

4.07

Height H (Metric)

103.4

Mounting Hole Centers (Imperial)

2.0

Material

Polyvinylchloride (PVC)

**Material Shortcut** 

PVC

Halogen Free

No

UV Resistant (Yes/No)

No

**Operating Temperature** 

+122°F (+50°C)

Reach Compliant (Article 33)

No

**ROHS Compliant** 

Yes

| Certification/Specification | UL EN 50085-2-3_1A CSA EN 50085-1:2005 + A1:2013 |
|-----------------------------|--|
| UL Recognized (US)          | Yes  |
|                             |  |
| Package Quantity (Imperial) | 30.0   |
| Package Quantity (Metric)   | 9.14   |
| Customs Number              | 3925900000                                       |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions